

**ULTRACUT 550** 

Page: 1

Compilation date: 08/12/2014

Revision No: 6

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: ULTRACUT 550

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metalworking Fluid

## 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington

Leeds

West Yorkshire LS26 8BS ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

### 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

#### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Lact.: H362

Classification under CHIP: N: R50/53; -: R64; -: R66

Most important adverse effects: May cause harm to breast-fed children. Very toxic to aquatic life. Very toxic to aquatic life

with long lasting effects.

## 2.2. Label elements

Label elements:

Hazard statements: H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS09: Environmental



**ULTRACUT 550** 

Page: 2

Precautionary statements: P264: Wash thoroughly after handling.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray. P270: Do not eat, drink or smoke when using this product.

P273: Avoid release to the environment.

P308+313: IF exposed or concerned: Get medical advice/attention.

P391: Collect spillage.

P501: Dispose of contents/container to local/national regulations.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

## **Hazardous ingredients:**

#### MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-090-8	64741-88-4	Substance with a Community	-	70-90%
		workplace exposure limit.		

#### C14-C17 CHLORINATED PARAFFIN - REACH registered number(s): 01-2119519269-33-XXXX

287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410;	10-30%	
			Aquatic Acute 1: H400		

## Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.Inhalation: There may be coughing and a sore throat.

4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Use water spray to cool containers. Suitable extinguishing media for the surrounding fire

should be used.

**ULTRACUT 550** 

Page: 3

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

## 6.4. Reference to other sections

#### Section 7: Handling and storage

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

#### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

**Hazardous ingredients:** 

### MINERAL OIL (NOTE L - LESS THAN 3% DMSO EXTRACT)

## Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5mg/m3	10mg/m3	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**ULTRACUT 550** 

Page: 4

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. **Respiratory protection:** Respiratory protection not normally required.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses with side-shields.

Skin protection: Protective clothing.

Environmental: No special requirement.

#### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-brown

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Viscous

Flash point°C: 200 Autoflammability°C: >300

Relative density: 0.9

# 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**ULTRACUT 550** 

Page: 5

#### **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

### **Hazardous ingredients:**

#### C14-C17 CHLORINATED PARAFFIN

					1
ORAL	∣RAT	LD50	> 2000	ma/ka	

Toxicity values: No data available.

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.Inhalation: There may be coughing and a sore throat.

### **Section 12: Ecological information**

#### 12.1. Toxicity

#### Hazardous ingredients:

#### C14-C17 CHLORINATED PARAFFIN

ALGAE	96H ErC50	>3.2	mg/l
Daphnia magna	48H EC50	0.006	mg/l
FISH	96H LC50	>5000	mg/l

### 12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

## 12.4. Mobility in soil

Mobility: Non-volatile. Absorbed only slowly into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

**ULTRACUT 550** 

Page: 6

### **Section 14: Transport information**

#### 14.1. UN number

UN number: UN3082

#### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(C14-C17 CHLORINATED PARAFFIN)

### 14.3. Transport hazard class(es)

Transport class: 9

#### 14.4. Packing group

Packing group: |||

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

#### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Phrases used in s.2 and s.3: H362: May cause harm to breast-fed children.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R64: May cause harm to breastfed babies.

R66: Repeated exposure may cause skin dryness or cracking.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration IC50 = median inhibitory concentration

dw = dry weight

## **ULTRACUT 550**

Page: 7

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.