1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name : Shell Flushing Oil 32

Uses : Process oil.

Product Code : 001B0421

Manufacturer/Supplier : Shell India Markets Private Limited

2nd Floor, Campus 4A RMZ Millenia Park

143 Dr. MGR Road, Perungudi

CHENNAI 600096 India

Telephone : (+91) 04443450000 (+91) 04443451516 Fax

Emergency Telephone

Number

: +91 22 6516 1058

2. COMPOSITION/INFORMATION ON INGREDIENTS

Preparation Description : Highly refined mineral oils and additives.

CAS No. 64742-54-7

Additional Information The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

3. HAZARDS IDENTIFICATION

EC Classification : Not classified as dangerous under EC criteria.

Health Hazards Not expected to be a health hazard when used under normal

> conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful

impurities.

Signs and Symptoms Oil acne/folliculitis signs and symptoms may include formation

of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

Safety Hazards Not classified as flammable but will burn.

Environmental Hazards Not classified as dangerous for the environment.

4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal

conditions.

Not applicable. Inhalation

Skin Contact : Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available. If persistent

1/7

irritation occurs, obtain medical attention.

Eye Contact : Flush eye with copious quantities of water. If persistent

irritation occurs, obtain medical attention.

Ingestion : If vomiting occurs spontaneously, keep head below hips to

prevent aspiration. Give nothing by mouth.

Advice to Physician : Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards : Hazardous combustion products may include: A complex

mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic

compounds.

Suitable Extinguishing

Media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing

Media

Do not use water in a jet.

Protective Equipment for

Firefighters

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures : Avoid contact with skin and eyes. Use appropriate containment

to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or

other appropriate barriers.

Clean Up Methods : Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional Advice : Local authorities should be advised if significant spillages

cannot be contained.

7. HANDLING AND STORAGE

General Precautions : Use local e

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of

this material

this material.

Handling : Avoid prolonged or repeated contact with skin. Avoid inhaling

vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment

should be used.

Storage : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labelled and closeable containers. Storage

2/7

Print Date 09.10.2011 00000002720 MSDS IN

Temperature: 0 - 50 °C / 32 - 122 °F

Recommended Materials For containers or container linings, use mild steel or high

density polyethylene.

Unsuitable Materials PVC.

Additional Information Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	IN OEL	TWA		5 mg/m3	
		[Mist.]			
	IN OEL	STEL		10 mg/m3	
		[Mist.]			
	ACGIH	TWA		5 mg/m3	
		[Inhalable			
		fraction.1			

Exposure Controls The level of protection and types of controls necessary will vary

depending upon potential exposure conditions. Select controls

based on a risk assessment of local circumstances.

Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or

mist formed, there is greater potential for airborne

concentrations to be generated.

Personal Protective Equipment

Personal protective equipment (PPE) should meet

recommended national standards. Check with PPE suppliers.

Respiratory Protection No respiratory protection is ordinarily required under normal

conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point

>65°C(149 °F)].

Hand Protection Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should

3/7

000000002720 Print Date 09.10.2011 MSDS IN

be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye Protection Wear safety glasses or full face shield if splashes are likely to

Skin protection not ordinarily required beyond standard issue **Protective Clothing**

work clothes.

Monitoring Methods Monitoring of the concentration of substances in the breathing

zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also

be appropriate.

Environmental Exposure

Controls

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Amber. Liquid at room temperature.

Odour Slight hydrocarbon. Not applicable. pΗ

Initial Boiling Point and

: $> 280 \,^{\circ}\text{C} / 536 \,^{\circ}\text{F}$ estimated value(s)

Boiling Range

Pour point Typical -15 °C / 5 °F

Flash point Typical 215 °C / 419 °F (COC)

Upper / lower Flammability

or Explosion limits

Typical 1 - 10 %(V) (based on mineral oil)

Auto-ignition temperature $: > 320 \, ^{\circ}\text{C} / 608 \, ^{\circ}\text{F}$ < 0.5 Pa at 20 °C / 68 °F (estimated value(s)) Vapour pressure

Density : Typical 865 kg/m3 at 15 °C / 59 °F

Water solubility : Negligible.

Solubility in other solvents : Data not available

n-octanol/water partition : > 6 (based on information on similar products)

coefficient (log Pow)

Dynamic viscosity : Data not available

Kinematic viscosity : Typical 30 mm2/s at 40 °C / 104 °F

Vapour density (air=1) : > 1 (estimated value(s)) Evaporation rate (nBuAc=1) : Data not available

10. STABILITY AND REACTIVITY

Stability Stable.

Extremes of temperature and direct sunlight. **Conditions to Avoid**

Materials to Avoid Strong oxidising agents.

Hazardous : Hazardous decomposition products are not expected to form

Decomposition Products during normal storage.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment : Information given is based on data on the components and the

toxicology of similar products.

Low toxicity: LD50 > 5000 mg/kg, Rat **Acute Oral Toxicity Acute Dermal Toxicity** Low toxicity: LD50 > 5000 mg/kg, Rabbit **Acute Inhalation Toxicity** Low toxicity: LC50 >5 mg/l / 4 h, Rat

Skin Irritation Expected to be slightly irritating. Prolonged or repeated skin

4/7

contact without proper cleaning can clog the pores of the skin

resulting in disorders such as oil acne/folliculitis.

Eye Irritation : Expected to be slightly irritating.

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the

: Not expected to be a hazard.

respiratory system.

Sensitisation : Not expected to be a skin sensitiser.

Repeated Dose Toxicity: Not expected to be a hazard.

Mutagenicity : Not considered a mutagenic hazard.Carcinogenicity : Product contains mineral oils of types shown to be non-

carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Reproductive and Developmental Toxicity Additional Information

: Used oils may contain harmful impurities that have

accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic

organisms. Practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to

aquatic organisms at concentrations less than 1 mg/l.

Microorganisms : Practically non toxic: LC/EC/IC50 > 100 mg/l

Mobility : Liquid under most environmental conditions. Floats on water. If

it enters soil, it will adsorb to soil particles and will not be

mobile.

Persistence/degradability : Major constituents are expected to be readily biodegradable,

but the product contains components that may persist in the

environment.

Bioaccumulation : Contains components with the potential to bioaccumulate.

Other Adverse Effects : Product is a mixture of non-volatile components, which are not

expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical

ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses.

Container Disposal : Dispose in accordance with prevailing regulations, preferably to

a recognised collector or contractor. The competence of the

5/7

Print Date 09.10.2011 00000002720 MSDS IN

Effective Date 30.09.2011

Material Safety Data Sheet

collector or contractor should be established beforehand.

Local Legislation : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification : Not classified as dangerous under EC criteria.

EC Symbols : No Hazard Symbol required

EC Risk Phrases : Not classified. EC Safety Phrases : Not classified.

Chemical Inventory Status

EINECS : All components

listed or polymer

exempt.

TSCA : All components

listed.

Other Information : The Manufacture, Storage and Import of Hazardous Chemicals

Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment)

Rules 1993.

16. OTHER INFORMATION

R-phrase(s)

Not classified.

MSDS Version Number : 1.1

MSDS Effective Date : 30.09.2011

6/7

Effective Date 30.09.2011

Material Safety Data Sheet

MSDS Revisions : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

MSDS Distribution : The information in this document should be made available to

all who may handle the product.

Disclaimer : This information is based on our current knowledge and is

intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property

of the product.