1. IDENTIFICATION OF THE SU Material Name Uses	:	TANCE/PREPARATION AND COMPANY/UNDERTAKING Shell Spirax S4 TXM Transmission oil.
Product Code	:	001D8246
Manufacturer/Supplier	:	Shell India Markets Private Limited 2nd Floor, Campus 4A RMZ Millenia Park 143 Dr. MGR Road, Perungudi CHENNAI 600096 India
Telephone Fax		(+91) 04443450000 (+91) 04443451516
Emergency Telephone Number	:	+91 22 6516 1058

2. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture Description : Highly refined mineral oils and additives.

Chemical Identity	CAS	EINECS	Symbol(s)	R-phrase(s)	Conc.
Zinc alkyl dithiophosphate	68649-42-3	272-028-3	Xi	R38; R52/53	1.00 - 3.00 %
Calcium sulphonate	68783-96-0	272-213-9		R53	1.00 - 3.00 %

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346. Refer to chapter 16 for full text of EC R-phrases.

3. HAZARDS IDENTIFICATION		
EC Classification	:	Not classified as dangerous under EC criteria.
Health Hazards	:	Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.
Signs and Symptoms	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Safety Hazards Environmental Hazards	:	Not classified as flammable but will burn. Not classified as dangerous for the environment.

Not expected to be a health hazard when used under normal conditions. No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice. Treat symptomatically.
 conditions. No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice. Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
 and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
irritation occurs, obtain medical attention. In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
are swallowed, however, get medical advice.
ency personnel.
Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases
(smoke). Carbon monoxide. Unidentified organic and inorganic
compounds.
Foam, water spray or fog. Dry chemical powder, carbon
dioxide, sand or earth may be used for small fires only.
Do not use water in a jet.
Proper protective equipment including breathing apparatus
must be worn when approaching a fire in a confined space.
URES eased material. For guidance on selection of personal protective
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or
 Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an
 s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay,
 s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
 s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay,
 Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages
 Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
s Material Safety Data Sheet. See Chapter 13 for information on local and international regulations. Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.

Handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Storage	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Store at ambient temperature.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Recommended Materials	:	For containers or container linings, use mild steel or high density polyethylene.
Unsuitable Materials	:	PVC.
Additional Information	:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA(Inhala ble fraction.)		5 mg/m3	
	IN OEL	TWA(Mist.)		5 mg/m3	
	IN OEL	STEL(Mist.)		10 mg/m3	

Biological Exposure Index (BEI)

No biological limit allocated.

Exposure Controls : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for

Personal Protective Equipment	subsequent recycle. Always observe good personal hy measures, such as washing hands after handling the r and before eating, drinking, and/or smoking. Routinely work clothing and protective equipment to remove contaminants. Discard contaminated clothing and foot cannot be cleaned. Practice good housekeeping. Personal protective equipment (PPE) should meet recommended national standards. Check with PPE su	material wash wear that
Respiratory Protection	No respiratory protection is ordinarily required under n conditions of use. In accordance with good industrial h practices, precautions should be taken to avoid breath material. If engineering controls do not maintain airbor concentrations to a level which is adequate to protect health, select respiratory protection equipment suitable specific conditions of use and meeting relevant legisla Check with respiratory protective equipment suppliers air-filtering respirators are suitable, select an appropria combination of mask and filter. Select a filter suitable f combined particulate/organic gases and vapours [boili >65°C(149 °F)].	aygiene ing of worker e for the tion. Where ate for ng point
Hand Protection	Where hand contact with the product may occur the us gloves approved to relevant standards (e.g. Europe: E US: F739) made from the following materials may pro- suitable chemical protection: PVC, neoprene or nitrile gloves. Suitability and durability of a glove is dependen- usage, e.g. frequency and duration of contact, chemic resistance of glove material, dexterity. Always seek ac from glove suppliers. Contaminated gloves should be Personal hygiene is a key element of effective hand ca Gloves must only be worn on clean hands. After using hands should be washed and dried thoroughly. Applica non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with pref- for > 480 minutes where suitable gloves can be identiff short-term/splash protection we recommend the same recognise that suitable gloves offering this level of pro- may not be available and in this case a lower breakthr time may be acceptable so long as appropriate mainter and replacement regimes are followed. Glove thickness a good predictor of glove resistance to a chemical as i dependent on the exact composition of the glove materi-	N374, vide rubber nt on al lvice replaced. are. gloves, ation of a erence ied. For , but tection ough enance as is not t is erial.
Eye Protection	Wear safety glasses or full face shield if splashes are occur.	
Protective Clothing	Skin protection not ordinarily required beyond standard work clothes.	dissue
Monitoring Methods	Monitoring of the concentration of substances in the be zone of workers or in the general workplace may be re confirm compliance with an OEL and adequacy of exp controls. For some substances biological monitoring m be appropriate. Validated exposure measurement met should be applied by a competent person and samples	equired to osure nay also hods

	analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.
Environmental Exposure Controls	 National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/ Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/ Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/ Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. PHYSICAL AND CHEMICAL	PROPERTIES
Appearance	: Amber. Liquid at room temperature.
Odour	: Slight hydrocarbon.
рН	: Not applicable.
Initial Boiling Point and	: > 280 °C / 536 °F estimated value(s)
Boiling Range	
Pour point	: Typical -42 °C / -44 °F
Flash point	: Typical 220 °C / 428 °F (COC)
Upper / lower Flammability	: Typical 1 - 10 %(V) (based on mineral oil)
or Explosion limits	
Auto-ignition temperature	: > 320 °C / 608 °F
Vapour pressure	: < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Specific gravity	: Typical 0.882 at 15 °C / 59 °F
Density	: Typical 882 kg/m3 at 15 °C / 59 °F
Water solubility	: Negligible.
Solubility in other solvents	: Data not available
n-octanol/water partition	: > 6 (based on information on similar products)
coefficient (log Pow)	
Dynamic viscosity	: Data not available
Kinematic viscosity	: Typical 60 mm2/s at 40 °C / 104 °F
Vapour density (air=1)	: > 1 (estimated value(s))
Electrical conductivity	: This material is not expected to be a static accumulator.
Evaporation rate (nBuAc=1)	: Data not available

10. STABILITY AND REACTIVITY Stability

	studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).
•	of types shown to be non-carcinogenic in animal skin-painting
:	Not expected to be carcinogenic. Product contains mineral oils
:	Not expected to be a hazard. Not considered a mutagenic hazard.
:	Not expected to be a skin sensitiser.
÷	Inhalation of vapours or mists may cause irritation.
:	Expected to be slightly irritating.
:	Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
:	Not considered to be an inhalation hazard under normal conditions of use.
:	Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit
:	Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
	Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
:	Information given is based on data on the components and the toxicology of similar products.
ΔΤΙ	ON
•	during normal storage.
÷	Strong oxidising agents. Hazardous decomposition products are not expected to form
:	Extremes of temperature and direct sunlight.
	· · · · · · · · · · · · · · · · · · ·

Material	:	Carcinogenicity Classification
Highly refined mineral oil	:	ACGIH Group A4: Not classifiable as a human carcinogen.
(IP346 <3%)		
Highly refined mineral oil	:	IARC 3: Not classifiable as to carcinogenicity to humans.
(IP346 <3%)		
Highly refined mineral oil	:	GHS / CLP: No carcinogenicity classification
(IP346 <3%)		

Reproductive and Developmental Toxicity	:	Not expected to be a hazard.
Additional Information	:	Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Acute Toxicity :		Poorly soluble	mixture.	May	cause	physical	fouling a	of	aquatic
------------------	--	----------------	----------	-----	-------	----------	-----------	----	---------

Microorganisms Mobility	:	organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract. Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l. Data not available Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on
Persistence/degradability	:	water. Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	:	Contains components with the potential to bioaccumulate.
Other Adverse Effects	:	Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
13. DISPOSAL CONSIDERATIO	NS	
Material Disposal	:	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	:	Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation	:	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

Additional Information : MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification EC Symbols EC Risk Phrases EC Safety Phrases	: : :	Not classified as dangerous under EC criteria. No Hazard Symbol required Not classified. Not classified.
Chemical Inventory Status		
EINECS	•	All components listed or polymer exempt.
TSCA	:	All components listed.
Other Information	:	The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

16. OTHER INFORMATION

R-phrase(s)

R38 R52/53 R53	Not classified. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the aquatic environment.			
SDS Version N	umber	:	1.2	
SDS Effective	Date	:	11.07.2013	
SDS Revisions	;	:	A vertical bar () in the left margin indicates an amendment from the previous version.	
SDS Distribution	on	:	The information in this document should be made available to all who may handle the product.	
Disclaimer		:	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.	