1. IDENTIFICATION OF THE SU Material Name Uses	JBSTANCE/PREPARATION AND COMPANY/UNDERTAKING : Shell Turbo Oil CC 32 : Turbine oil.
Product Code	: 001A9047
Manufacturer/Supplier	 Shell India Markets Private Limited 2nd Floor, Campus 4A RMZ Millenia Park 143 Dr. MGR Road, Perungudi CHENNAI 600096 India
Telephone Fax	: (+91) 04443450000 : (+91) 04443451516
Emergency Telephone Number	: +91 22 6516 1058
2. COMPOSITION/INFORMATI	ON ON INGREDIENTS
	: Highly refined mineral oils and additives.
Additional Information	: The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
3. HAZARDS IDENTIFICATION	
EC Classification	: Not classified as dangerous under EC criteria.
Health Hazards	Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.
Signs and Symptoms	 Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Safety Hazards Environmental Hazards	 Not classified as flammable but will burn. Not classified as dangerous for the environment.
4. FIRST AID MEASURES	
General Information	 Not expected to be a health hazard when used under normal conditions.
Inhalation	 No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent

Eye Contact	 irritation occurs, obtain medical attention. Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	 In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician	: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media Unsuitable Extinguishing	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.
Media	•	Do not use water in a jet.
Protective Equipment for Firefighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures Clean Up Methods Additional Advice	:	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
7. HANDLING AND STORAGE		
General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Storage	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage
		2/7

		Temperature: 0 - 50 °C / 32 - 122 °F
Recommended Materials	:	For containers or container linings, use mild steel or high
		density polyethylene.
Unsuitable Materials	:	PVC.
Additional Information	:	Polyethylene containers should not be exposed to high
		temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	IN OEL	TWA		5 mg/m3	
		[Mist.]			
	IN OEL	STEL		10 mg/m3	
		[Mist.]			
	ACGIH	TWA		5 mg/m3	
		[Inhalable			
		fraction.]			
Exposure Contro Personal Protect		depending up based on a ris Appropriate n airborne conc mist formed, t concentration Personal prot	on potential sk assessme neasures incl entrations. V here is great s to be gene ective equipr	exposure condition int of local circums lude: Adequate ve Vhere material is h ter potential for airl rated. ment (PPE) should	ntilation to control leated, sprayed or borne
Equipment		recommende	d national sta	andards. Check wi	th PPE suppliers.
Respiratory P		conditions of practices, pre material. If en concentration health, select specific condi Check with re air-filtering re combination of combined par >65°C(149 °F	use. In accor cautions sho gineering co s to a level w respiratory p tions of use a spiratory pro spirators are of mask and f ticulate/orga		ndustrial hygiene oid breathing of tain airborne to protect worker ent suitable for the ant legislation. suppliers. Where appropriate suitable for ours [boiling point
Hand Protecti	ion :	gloves approv US: F739) ma suitable chem gloves. Suital usage, e.g. fr resistance of	ved to relevant ade from the nical protection pility and dura equency and glove materia		Europe: EN374, s may provide o or nitrile rubber dependent on

		be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection	:	Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	:	Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods Environmental Exposure Controls	:	Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
9. PHYSICAL AND CHEMICAL	PR	OPERTIES
Appearance	:	Amber. Liquid at room temperature.
Odour	:	Slight hydrocarbon.
pН	:	Not applicable.
Initial Boiling Point and	•	> 280 °C / 536 °E estimated value(s)

Odour	: Slight hydrocarbon.
рН	: Not applicable.
Initial Boiling Point and	: > 280 °C / 536 °F estimated value(s)
Boiling Range	
Pour point	: Typical -12 °C / 10 °F
Flash point	: Typical 218 °C / 424 °F (COC)
Upper / lower Flammability or Explosion limits	: Typical 1 - 10 %(V) (based on mineral oil)
Auto-ignition temperature	: > 320 °C / 608 °F
Vapour pressure	: < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Specific gravity	: Data not available
Density	: Data not available
Water solubility	: Negligible.
Solubility in other solvents	
n-octanol/water partition	: > 6 (based on information on similar products)
coefficient (log Pow)	
Dynamic viscosity	: Data not available
Kinematic viscosity	: Typical 32 mm2/s at 40 °C / 104 °F
Vapour density (air=1)	: > 1 (estimated value(s))
Evaporation rate (nBuAc=1)	: Data not available
10. STABILITY AND REACTIVIT	
Stability	: Stable.
Conditions to Avoid	: Extremes of temperature and direct sunlight.
Materials to Avoid	: Strong oxidising agents.
Hazardous	: Hazardous decomposition products are not expected to form
Decomposition Products	during normal storage.
11. TOXICOLOGICAL INFORMA	-
Basis for Assessment	: Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit

Skin Irritation Eye Irritation Respiratory Irritation Sensitisation Repeated Dose Toxicity Mutagenicity Carcinogenicity	 conditions of use. Expected to be slightly irritating. Expected to be slightly irritating. Inhalation of vapours or mists may cause irritation. Not expected to be a skin sensitiser. Not expected to be a hazard. Not considered a mutagenic hazard. Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
Reproductive and Developmental Toxicity Additional Information	 Not expected to be a hazard. Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled
	with caution and skin contact avoided as far as possible. DN Not been determined specifically for this product. Information given is components and the ecotoxicology of similar products.
Acute Toxicity	: Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic
Microorganisms Mobility	 effects to aquatic organisms at concentrations less than 1 mg/l. Data not available Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Persistence/degradability	 Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	: Contains components with the potential to bioaccumulate.
Other Adverse Effects	: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
13. DISPOSAL CONSIDERATIO Material Disposal	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	: Dispose in accordance with prevailing regulations, preferably to
Print Date 09.10.2011	5/7 0000000304

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification EC Symbols EC Risk Phrases EC Safety Phrases Chemical Inventory Status	: : :	Not classified as dangerous under EC criteria. No Hazard Symbol required Not classified. Not classified.
EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
Other Information	:	The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

16. OTHER INFORMATION

R-phrase(s)

Not classified.

MSDS Version Number : 1.1

MSDS Effective Date : 30.09.2011

MSDS Revisions	: A vertical bar () in the left margin indicates an amendment from the previous version.
MSDS Distribution	: The information in this document should be made available to all who may handle the product.
Disclaimer	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.