

09-JAN-09
LIPLEXA MEP 2 TUBES (FORMER

To Whom It May Concern:

As you requested, attached is a copy of a Material Safety Data Sheet covering (our ref. no. 800317) LIPLEXA MEP 2 TUBES (FORMER S 1054).

Title III of the Superfund Amendments and Reauthorizations Act (SARA) requires chemical suppliers of mixtures and trade name products to provide information to their customers sufficient for them to comply with the requirements of Section 313.

Material Safety Data Sheets (MSDS's) have been updated to include the section 313 information.

Erick Aho
Chemist

TOTAL Lubricants USA, Inc.
 Airport Road
 Rockingham NC 28379-1058

REVISION DATE
 28-OCT-04

DATE ISSUED
 09-JAN-09

IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME: LIPLEXA MEP 2 TUBES (FORMER S 1054)	PRODUCT #: 800315
CHEMICAL NAME: N/A - Mixture	CAS #'S: Mixture
PRODUCT APPEARANCE AND ODOR: Smooth grey grease, petroleum odor	CHEMICAL FAMILY: Petroleum hydrocarbon
SYNONYMS: Petroleum-based lithium grease	EMERGENCY TELEPHONE: 910-997-5086

COMPONENTS AND HAZARD INFORMATION

COMPONENTS:	W/W	HAZARD DATA (TLV, LD50, LC50, ETC.):
Petroleum-based lubricating oil CAS # 64742-52-5		TLV 5 mg/meter cubed (as an oil mist)
Lithium complex soap thickeners CAS # n/a		n/e
Antimony dialkylphosphorodithioate CAS # 15874-48-3		n/e
Proprietary additives		

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):

Health	Flammability	Reactivity
1	1	0

TRANSPORTATION INFORMATION

TRANSPORTATION/SHIPPING INFORMATION:

Department of Transportation (DOT): Not regulated

EMERGENCY FIRST AID

EYE CONTACT:
 If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT:
 In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

INHALATION:
 Vapor pressure is very low. Vapor inhalation under ambient conditions is

TOTAL Lubricants USA, Inc.
Airport Road
Rockingham NC 28379-1058

REVISION DATE
28-OCT-04

DATE ISSUED
09-JAN-09

EMERGENCY FIRST AID

normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation; administer oxygen if available. If overexposure to oil mist, remove from further exposure until excessive oil mist condition subsides.

INGESTION:

If ingested, do not induce vomiting. Call a physician immediately.

FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT (MINIMUM): 400°F METHOD: C.O.C.
AUTOIGNITION TEMPERATURE: N/E

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION:

Health	Flammability	Reactivity
1	1	0

FLAMMABLE OR EXPLOSIVE LIMITS (approximate percent by volume in air):
Estimated values: lower N/E upper N/E

FLAMMABILITY CLASSIFICATION: Not flammable

EXITINGUISHING MEDIA: Agents approved for Class B (e.g., dry chemical CO₂, foam, steam) or water fog.

FIRE FIGHTING EQUIPMENT: Firefighters should wear full bunker gear, including a positive self-contained breathing apparatus.

HAZARDOUS COMBUSTION PRODUCTS: Incomplete burning can produce carbon monoxide and/or carbon dioxide and other harmful products.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
not applicable

"EMPTY" CONTAINER WARNING:

Empty containers retain residue (liquid or vapor) and can be dangerous. DO NOT PRESSURIZE, WELD, CUT BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged, and returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with government regulations.

HEALTH AND HAZARD INFORMATION

EXPOSURE LIMIT FOR TOTAL PRODUCT: Monitor data listed in the Components and Hazard Information section.

VARIABILITY AMONG INDIVIDUALS:

Health studies have shown that many petroleum hydrocarbons and synthetic

TOTAL Lubricants USA, Inc.
 Airport Road
 Rockingham NC 28379-1058

REVISION DATE
 28-OCT-04

DATE ISSUED
 09-JAN-09

HEALTH AND HAZARD INFORMATION

lubricants pose potential human health risks which vary from person to person. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.
 EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure):
 Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis.
 Product contacting the eye may cause irritation.
 Product has a low order of oral and dermal toxicity.
 Possible aspiration hazard.
 Induced vomiting may cause aspiration of product into the lungs.
 (See Emergency First Aid Section).

PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes.

BOILING RANGE:
 Wide range

VAPOR PRESSURE:
 < 0.1 @ 38°C/100°F

SPECIFIC GRAVITY (25°C/25°C):
 (WATER = 1)
 < 1.0

VAPOR DENSITY (AIR = 1):
 > 8

MOLECULAR WEIGHT:
 Wide range

PERCENT VOLATILE BY VOLUME:
 Negligible

EVAPORATION RATE @ 1 ATM. AND 25°C
 (77°F) (n-BUTYL ACETATE = 1):
 < 1.0

SOLUBILITY IN WATER @ 1 ATM. and 25°C
 (77°F):
 Negligible

POUR, CONGEALING OR MELTING POINT:
 n/e

FREEZING POINT:
 n/e

REACTIVITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite, etc., as this represents a serious explosion hazard.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:
 Fumes, smoke, carbon monoxide, oxides of sulfur, and other decomposition products, in case of incomplete combustion.

CONDITIONS TO AVOID:
 Open flames.

MATERIAL SAFETY DATA SHEET FOR LIPLIXA MEP 2 TUBES (FORMER S 1054)

TOTAL Lubricants USA, Inc.
Airport Road
Rockingham NC 28379-1058

REVISION DATE
28-OCT-04

DATE ISSUED
09-JAN-09

TOXICITY

ORAL (Acute)	N/E						
DERMAL (Acute)	N/E						
EYE	N/E						
INHALATION (Acute)	N/E						
CHRONIC, SUBCHRONIC, ETC.	N/E						
Medical Conditions Aggravated by Exposure: Unknown							
This product does NOT contain any ingredients identified as carcinogenic by IARC, NTP, or OSHA.							
SARA Section 313 Status:	This product contains the following Section 313 reportable ingredients:						
	<table><thead><tr><th>Component</th><th>CAS #</th><th>%</th></tr></thead><tbody><tr><td>Antimony compounds</td><td>n/a</td><td>5 max.</td></tr></tbody></table>	Component	CAS #	%	Antimony compounds	n/a	5 max.
Component	CAS #	%					
Antimony compounds	n/a	5 max.					

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Keep product out of sewers and watercourses by diking or impounding. Absorb with sand or inert material. Sweep or scoop up and remove. Prevent spread of spill. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with local regulations.

WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for proper disposal procedures.)
Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

PROTECTION AND PRECAUTIONS

VENTILATION: (Always maintain below permissible exposure limits.)
Use local exhaust to capture vapor, mist or fumes, if necessary.
Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air.

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.)
Normally not needed at ambient temperatures. Use supplied air respiratory protection in confined or enclosed spaces, if needed. Use filter, dust, fume, or mist respirator type under misting conditions. Use can or cartridge; gas or vapor respirator type under conditions exceeding TWA standard.

PROTECTIVE GLOVES:
Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:
Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:
Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

TOTAL Lubricants USA, Inc.
Airport Road
Rockingham NC 28379-1058

REVISION DATE
28-OCT-04

DATE ISSUED
09-JAN-09

PROTECTION AND PRECAUTIONS

WORK PRACTICES/ENGINEERING CONTROLS:

Keep containers closed when not in use. Do not handle near heat, sparks, flame or strong oxidants.

PERSONAL HYGIENE:

Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

PREPARED BY: Erick Aho

CHEMIST

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA RELEVANT TO HIS PARTICULAR USE.