12-JAN-09 MARTOL 5088 S

To Whom It May Concern:

As you requested, attached is a copy of a Material Safety Data Sheet covering (our ref. no. 202057) MARTOL 5088 S.

Title III of the Superfund Amendments and Reauthorizations Act (SARA) requires chemical suppliers of mixtures and trade name products to provide information to their customers sufficient for them to comply with the requirements of Section 313.

Material Safety Data Sheets (MSDS's) have been updated to include the section 313 information.

Erick Aho Chemist TOTAL Lubricants USA, Inc. Airport Road Rockingham NC 28379-1058

REVISION DATE 03-NOV-05

DATE ISSUED 12-JAN-09

IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME: PRODUCT #: MARTOL 5088 S 202057

CHEMICAL NAME: CAS #'S: N/A - Mixture Mixture

PRODUCT APPEARANCE AND ODOR: CHEMICAL FAMILY:

Light amber liquid, petroleum odor Petroleum hydrocarbon

SYNONYMS: EMERGENCY TELEPHONE:

Petroleum-based metal forming oil 910-997-5086

COMPONENTS AND HAZARD INFORMATION

COMPONENTS: W/W HAZARD DATA (TLV, LD50, LC50, ETC.):

Petroleum based lubricating oil 5 mg/m3 ACGIH/OSHA TWA

CAS No. 64742-62-7, 64742-65-0 (as an oil mist)

Canola oil n/e

CAS No. 120962-03-0

Ethylene-propylene copolymer n/e CAS No. 9010-79-1

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):

Health Flammability Reactivity
1 1 0

TRANSPORTATION INFORMATION

TRANSPORTATION/SHIPPING INFORMATION:

Department of Transportation (DOT): Not regulated

EMERGENCY FIRST AID

EYE CONTACT:

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT:

In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

INHALATION:

Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has

MATERIAL SAFETY DATA SHEET FOR MARTOL 5088 S

TOTAL Lubricants USA, Inc. Airport Road Rockingham NC 28379-1058

REVISION DATE 03-NOV-05

DATE ISSUED 12-JAN-09

EMERGENCY FIRST AID

stopped, start resuscitation; administer oxygen if available. If overexposure to oil mist, remove from further exposure until excessive oil mist condition subsides.

INGESTION:

If ingested, do not induce vomiting. Call a physician immediately.

FIRE AND EXPLOSION HAZARD INFORMATION

AUTOIGNITION TEMPERATURE: FLASH POINT (MINIMUM):

>480'F Test method: COC N/E

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION:

Flammability Reactivity Health 1

FLAMMABLE OR EXPLOSIVE LIMITS (approximate percent by volume in air): Estimated values: lower N/E upper N/E

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES:

Foam, CO2, Dry chemical. Use water spray to cool surface of container. Use self contained breathing apparatus, avoid breathing fumes, vapors, or mists. Water may cause frothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: n/a

HEALTH AND HAZARD INFORMATION

EXPOSURE LIMIT FOR TOTAL PRODUCT: Monitor data listed in the Components and Hazard Information section.

VARIABILITY AMONG INDIVIDUALS:

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which vary from person to person. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure):

Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis.

Product contacting the eye may cause irritation.

Product has a low order of oral and dermal toxicity.

Possible aspiration hazard.

Induced vomiting may cause aspiration of product into the lungs. (See Emergency First Aid Section).

PHYSICAL DATA

The following data are approximate or typical values and should not be used

TOTAL Lubricants USA, Inc. Airport Road Rockingham NC 28379-1058

REVISION DATE 03-NOV-05

DATE ISSUED 12-JAN-09

PHYSICAL DATA

for precise design purposes. BOILING RANGE:

Not available

SPECIFIC GRAVITY (25°C/25°C):

(WATER = 1)

< 1.0

MOLECULAR WEIGHT:

Wide range

EVAPORATION RATE @ 1 ATM. AND 25°C

Not available

(n-BUTYL ACETATE = 1):

VAPOR PRESSURE:

< 0.1 mmHq @ 20°C

VAPOR DENSITY (AIR = 1):

PERCENT VOLATILE BY VOLUME:

Negligible

SOLUBILITY IN WATER @ 1 ATM. and 25°C

(77°F): Nil

REACTIVITY

TOXICITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite, etc., as this represents an explosion hazard.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:

Fumes, smoke, carbon monoxide, and other deomposition products, in case of incomplete combustion.

CONDITIONS TO AVOID: Open flames.

ORAL (Acute)	N/E
DERMAL (Acute) EYE	N/E N/E
INHALATION (Acute)	n/E

Medical Conditions Aggravated by Exposure: Unknown

N/E

This product does NOT contain any ingredients identified as carcinogenic by IARC, NTP, or OSHA.

All components known to be contained in this product are on the TSCA inventory or are exempt.

SARA Section 313 Status:

CHRONIC, SUBCHRONIC, ETC.

This material is not known to contain any chemicals on the SARA Section 313 list at a concentration greater than 1.0 percent or carcinogenic chemical on that list at a concentration greater than 0.1 percent.

TOTAL Lubricants USA, Inc. Airport Road Rockingham NC 28379-1058

REVISION DATE 03-NOV-05

DATE ISSUED

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Keep product out of sewers and watercourses by diking or impounding. Absorb
with sand or inert material. Sweep or scoop up and remove. Prevent spread
of spill. Advise authorities if product has entered or may enter sewers,
watercourses or extensive land areas. Assure conformity with local regulations.
WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for
proper disposal procedures.)

Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

PROTECTION AND PRECAUTIONS

VENTILATION: (Always maintain below permissible exposure limits.)
Use local exhaust to capture vapor, mist or fumes, if necessary.
Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air.

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.)
Normally not needed at ambient temperatures. Use supplied air respiratory
protection in confined or enclosed spaces, if needed. Use filter, dust, fume,
or mist respirator type under misting conditions. Use can or cartridge; gas
or vapor respirator type under conditions exceeding TWA standard.

PROTECTIVE GLOVES:

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS:

Keep containers closed when not in use. Do not handle near heat, sparks, flame or strong oxidants.

PERSONAL HYGIENE:

Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oilsoaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

PREPARED BY: Erick Aho CHEMIST

MATERIAL SAFETY DATA SHEET FOR MARTOL 5088 S

TOTAL Lubricants USA, Inc. Airport Road Rockingham NC 28379-1058

REVISION DATE 03-NOV-05

DATE ISSUED 12-JAN-09

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA RELEVANT TO HIS PARTICULAR USE.