

**MATERIAL SAFETY DATA SHEET**

TOTAL Specialties USA, Inc.. 5 N. Stiles Street, Linden NJ 07036  
Phone 1-908-862-9300



Product REFRIGERATION OIL 300  
ORIGINAL ISSUE May 10-2010  
REVISION DATE Nov 4, 2013

**IDENTIFICATION AND EMERGENCY INFORMATION**

PRODUCT NAME: REFRIGERATION OIL 300  
REFRIGERATION OIL 300  
(Apx ISO 68)

PRODUCT #:

CHEMICAL NAME: Severely hydrotreated naphthenic oil

CAS #'S: 64742-52-5

PRODUCT APPEARANCE AND ODOR: Amber liquid, petroleum odor

CHEMICAL FAMILY: Petroleum hydrocarbon

SYNONYMS: Naphthenic refrigeration oil

EMERGENCY TELEPHONE: 1-800-442-5823 or 1-908-862-9300

**COMPONENTS AND HAZARD INFORMATION**

COMPONENTS: W/W HAZARD DATA (TLV, LD50, LC50, ETC.):  
Petroleum based lubricating oil 5 mg/m3 TWA (OSHA, ACGIH)  
CAS# 64742-53-6, 64742-52-5\*

-----  
\* Naphthenic base oil used are not limited to but include these CAS numbers.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):  
Health Flammability Reactivity  
0 1 0

**TRANSPORTATION INFORMATION**

TRANSPORTATION/SHIPPING INFORMATION:

Department of Transportation (DOT): Not regulated

**EMERGENCY FIRST AID**

EYE CONTACT:  
If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT:  
As with all petroleum products, if this product contacts skin, wash affected area thoroughly with soap and water to prevent irritations from occurring. Oil soaked clothing should be removed and laundered frequently to minimize skin contact with product. Prolonged contact with skin may cause irritation.

INHALATION:  
Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation; administer oxygen if available. If overexposure to oil mist, remove from further exposure until excessive oil mist condition subsides.

INGESTION:

## FIRE AND EXPLOSION HAZARD INFORMATION

## HEALTH AND HAZARD INFORMATION

PHYSICAL DATA

## MOLECULAR WEIGHT:

Wide range

## PERCENT VOLATILE BY VOLUME:

Negligible

## EVAPORATION RATE @ 1 ATM. AND 25°C

(77°F) (n-BUTYL ACETATE = 1):

&lt; 1.0

## SOLUBILITY IN WATER @ 1 ATM. and 25°C

(77°F):

Negligible

## POUR, CONGEALING OR MELTING POINT:

n/e

## FREEZING POINT:

n/e

## REACTIVITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

## DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:

Fumes, smoke, carbon monoxide and other decomposition products, in case of incomplete combustion.

## CONDITIONS TO AVOID:

Open flames.

## TOXICITY

ORAL (Acute)

N/E

DERMAL (Acute)

N/E

EYE

N/E

INHALATION (Acute)

N/E

CHRONIC, SUBCHRONIC, ETC.

N/E

Medical Conditions Aggravated by Exposure: Unknown

This product does NOT contain any ingredients identified as carcinogenic by IARC, NTP, or OSHA.

SARA Section 313 Status: This material is not known to contain any chemicals on the SARA Section 313 list at a concentration greater than 1.0 percent or carcinogenic chemical on that list at a concentration greater than 0.1 percent.

## SPILL OR LEAK PROCEDURES

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep product out of sewers and watercourses by diking or impounding. Absorb with sand or inert material. Sweep or scoop up and remove. Prevent spread of spill. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with local regulations.

WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for proper disposal procedures.) Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

## PROTECTION AND PRECAUTIONS

VENTILATION: (Always maintain below permissible exposure limits.)

Use local exhaust to capture vapor, mist or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition source

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.)

Normally not needed at ambient temperatures. Use supplied air respiratory protection in confined or enclosed spaces, if needed. Use filter, dust, fume, or mist respirator type under misting conditions. Use can or cartridge; gas or vapor respirator type under conditions exceeding TWA standard.

**PROTECTIVE GLOVES:**

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

**EYE PROTECTION:**

Use splash goggles or face shield when eye contact may occur.

**OTHER PROTECTIVE EQUIPMENT:**

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

**WORK PRACTICES/ENGINEERING CONTROLS:**

Keep containers closed when not in use. Do not handle near heat, sparks, flame, or strong oxidants.

**PERSONAL HYGIENE:**

Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

**OTHER REGULATORY INFORMATION**

**OSH HAZARD DETERMINATION:** This material is not known to be hazardous as defined by OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Inventory:** All of the components of this material are listed on the Toxic Chemical Substances Inventory. This product is in compliance with the Toxic Substances control Act (TSCA).

**SARA SECTION 311 - HAZARD CATEGORIES:**

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below:

NO	<b>IMMEDIATE (ACUTE) HEALTH HAZARD</b>	NO	<b>SUDDEN RELEASE OF PRESSURE HAZARD</b>
NO	<b>DELAYED (CHRONIC) HEALTH HAZARD</b>	NO	<b>REACTIVE HAZARD</b>
NO	<b>FIRE HAZARD</b>		

**SARA 302/304:** There are no components in this product on the SARA 302/304 list.

**SARA SECTION 313 - TOXIC COMPONENTS:** This product does not contain >1.0% (greater than 0.1% for carcinogenic substance) of any chemical substances listed under SARA Section 313.

**CLEAN WATER ACT (CWA):**

Under the CWA, discharges of fluids to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802.

**CERCLA HAZARDOUS SUBSTANCES:**

As defined by CERCLA, the term "hazardous substance" does not include any ingredients or fraction thereof, which is not otherwise specifically listed or designated as a hazardous substance.

**CALIFORNIA PROPOSITION 65**

This product contains no ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute.

**NEW JERSEY RIGHT-TO-KNOW LABEL**

Mineral oil

**WHMIS CLASSIFICATION**

This product is not a WHMIS controlled substance.

PREPARED BY: Alan Denniston

Technical Services

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA RELEVANT TO HIS PARTICULAR USE.