

MATERIAL SAFETY DATA SHEET

TOTAL Specialties USA, Inc.. 5 N. Stiles Street, Linden NJ 07036
Phone 1-908-862-9300



Product SYNTHETIC NG COMPRESSOR OIL
ORIGINAL ISSUE June 29, 2011
REVISION DATE Nov 4, 2013

IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME: SYNTHETIC NG COMPRESSOR OIL (ISO 68 to 150)
PRODUCT #:

CHEMICAL NAME: N/A - Mixture
CAS #'S: Mixture

PRODUCT APPEARANCE AND ODOR: Amber liquid, mild odor
CHEMICAL FAMILY: N/A

SYNONYMS: PAG Gas compressor fluid
EMERGENCY TELEPHONE: 1-908-862-9300

COMPONENTS AND HAZARD INFORMATION

COMPONENTS	CAS NO.	%	HAZARD DATA
Oxirane, methyl-, polyalkylene glycol polymer	9038-95-3		

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS):
Health 1 Flammability 1 Reactivity 0

TRANSPORTATION INFORMATION

TRANSPORTATION/SHIPPING INFORMATION:

Department of Transportation (DOT): Not regulated

EMERGENCY FIRST AID**EYE CONTACT:**

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN CONTACT:

In case of skin contact, remove contaminated clothing and wash skin thoroughly with soap and water.

INHALATION:

Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician. If breathing is irregular or has stopped, start resuscitation; administer oxygen if available. If overexposure to oil mist, remove from further exposure until excessive oil mist condition subsides.

INGESTION:

If ingested, do not induce vomiting. Call a physician immediately.

FIRE AND EXPLOSION HAZARD INFORMATION

FLASH POINT (MINIMUM):

>204°C (>400°F) Test method: COC

AUTOIGNITION TEMPERATURE:

N/E

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION:

Health	Flammability	Reactivity
1	1	0

FLAMMABLE OR EXPLOSIVE LIMITS (approximate percent by volume in air):

Estimated values: lower N/E upper N/E

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES:

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type product, depending on size or potential size of fire and circumstances

related to the situation. Water or foam may cause frothing.

Use water to keep fire-exposed containers cool. Water froth may be used to flush spills away from exposure. Minimize breathing gases, vapor, fumes, or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

n/a

"EMPTY" CONTAINER WARNING:

Empty containers retain residue (liquid or vapor) and can be dangerous. DO NOT PRESSURIZE, WELD, CUT BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged, and returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with government regulations.

HEALTH AND HAZARD INFORMATION

EXPOSURE LIMIT FOR TOTAL PRODUCT: Monitor data listed in the Components and Hazard Information section.

VARIABILITY AMONG INDIVIDUALS:

Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which vary from person to person. As a precaution, exposure to liquids, vapors, mists, or fumes should be minimized.

EFFECTS OF OVEREXPOSURE (Signs and symptoms of exposure):

Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis. Product contacting the eye may cause irritation. Product has a low order of oral and dermal toxicity. Possible aspiration hazard. Induced vomiting may cause aspiration of product into the lungs. (See Emergency First Aid Section).

PHYSICAL DATA

The following data are approximate or typical values and should not be used for precise design purposes.

BOILING RANGE:

Not available

VAPOR PRESSURE:

< 0.1 mmHg @ 20°C

SPECIFIC GRAVITY (25°C/25°C):

(WATER = 1)

1.04

VAPOR DENSITY (AIR = 1):

> 5

MOLECULAR WEIGHT:

Wide range

PERCENT VOLATILE BY VOLUME:

Negligible

EVAPORATION RATE @ 1 ATM. AND 25°C

(77°F) (n-BUTYL ACETATE = 1):

Not available

SOLUBILITY IN WATER @ 1 ATM. and 25°C

(77°F):

Soluble

REACTIVITY

This product is stable and will NOT react violently with water. Hazardous polymerization will not occur. Avoid contact with strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite, etc., as this represents an explosion hazard.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS:

Fumes, smoke, carbon monoxide, and other decomposition products, in case of incomplete combustion.

CONDITIONS TO AVOID:

Open flames.

TOXICITY

ORAL (Acute)

N/E

DERMAL (Acute)

N/E

EYE

N/E

INHALATION (Acute)

N/E

CHRONIC, SUBCHRONIC, ETC.

N/E

Medical Conditions Aggravated by Exposure: Unknown

This product does NOT contain any ingredients identified as carcinogenic by IARC, NTP, or OSHA. All components known to be contained in this product are on the TSCA inventory or are exempt.

SARA Section 313 Status: This material is not known to contain any chemicals on the SARA Section 313 list at a concentration greater than 1.0 percent or carcinogenic chemical on that list at a concentration greater than 0.1 percent.

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep product out of sewers and watercourses by diking or impounding. Absorb with sand or inert material. Sweep or scoop up and remove. Prevent spread of spill. Advise authorities if product has entered or may enter sewers,

watercourses or extensive land areas. Assure conformity with local regulations.

WASTE DISPOSAL METHOD: (Consult federal, state, or local authorities for proper disposal procedures.) Assure conformity with applicable disposal regulations. Dispose of absorbed material at an approved waste site or facility.

PROTECTION AND PRECAUTIONS

VENTILATION: (Always maintain below permissible exposure limits.) Use local exhaust to capture vapor, mist or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air.

RESPIRATORY PROTECTION: (Use only NIOSH approved equipment.) Normally not needed at ambient temperatures. Use supplied air respiratory protection in confined or enclosed spaces, if needed. Use filter, dust, fume, or mist respirator type under misting conditions. Use can or cartridge; gas or vapor respirator type under conditions exceeding TWA standard.

PROTECTIVE GLOVES:
Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION:
Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT:
Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS:
Keep containers closed when not in use. Do not handle near heat, sparks , flame or strong oxidants.

PERSONAL HYGIENE:
Minimize breathing vapor, mist, or fumes. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean before reuse; discard if oil-soaked. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is readily removed from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

OTHER REGULATORY INFORMATION

SARA SECTION 311 - HAZARD CATEGORIES:

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below: None.

NO	IMMEDIATE (ACUTE) HEALTH HAZARD	NO	SUDDEN RELEASE OF PRESSURE HAZARD
NO	DELAYED (CHRONIC) HEALTH HAZARD	NO	REACTIVE HAZARD
NO	FIRE HAZARD		

SARA SECTION 302 - EXTREMELY HAZARDOUS WASTE:

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40 CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

CLEAN WATER ACT (CWA):

Under the CWA, discharges of crude oil and petroleum products to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802.

CERCLA HAZARDOUS SUBSTANCES:

No components of these products are specifically listed as hazardous substances in 40 CFR 302.4 (unlisted hazardous substances are not identified) or are present at levels which could require reporting.

U.S. TSCA INVENTORY

All components of this material are listed on the U.S. TSCA Inventory.

CALIFORNIA PROPOSITION 65

WARNING. This product contains the following chemical(s) known to the State of California to cause cancer: None.

CALIFORNIA SCAQMD rule 443.1 (South Coast Air Quality Management District, labeling of materials containing organic solvents): Not applicable. None.

NEW JERSEY RIGHT-TO-KNOW LABEL

Lubricating fluid

Pennsylvania (Worker & community right to know act): This product is subject to the worker and community right to know act. This product contains no known components which could require identification in the MSDS.

Massachusetts (Hazardous Substances Disclosure by Employers): the following components of this product appear on the Massachusetts Substance List and are present at levels which should require identification on the MSDS: None.

ADDITIONAL REGULATORY REMARKS

None

PREPARED BY: Alan Denniston

Technical Services

THE ABOVE INFORMATION IS ACCURATE TO THE BEST OF OUR KNOWLEDGE. HOWEVER, SINCE DATA, SAFETY STANDARDS, AND GOVERNMENT REGULATIONS ARE SUBJECT TO CHANGE AND THE CONDITIONS OF HANDLING AND USE, OR MISUSE BEYOND OUR CONTROL, SELLER MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. USER SHOULD SATISFY HIMSELF THAT HE HAS ALL CURRENT DATA RELEVANT TO HIS PARTICULAR USE.