ASHLAND	
SAFETY DATA SHEET	

Page: 1

Revision Date: 05/21/2015

Print Date: 6/29/2015 SDS Number: R0296766

Version: 1.0

Zerex[™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

 Zerex™ G-05 ANTIFREEZE COOLANT
 ™ Trademark, Ashland or its subsidiaries, registered in various countries

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification	
Acute toxicity (Oral)	: Category 4
Reproductive toxicity	: Category 1B
Specific target organ systemic toxicity - repeated exposure (Oral)	: Category 2 (Kidney, Liver)
GHS Label element	
Hazard pictograms	
Signal Word	: Danger
Hazard Statements	 Harmful if swallowed. May damage fertility or the unborn child. May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.
Precautionary Statements	: Prevention:
	1 / 18

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex™ G-05 ANTIFREEZE COOLANT	Version: 1.0
[™] Trademark, Ashland or its subsidiaries, registered	
in various countries	
857949	

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection. **Response:** IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. IF exposed or concerned: Get medical advice/ attention. Storage: Store locked up. Disposal: Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302	94.07
		STOT RE 2; H373	
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302	4.70
		STOT RE 2; H373	
SODIUM BENZOATE	532-32-1	Eye Irrit. 2A; H319	2.59
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	Repr. 1B; H360	1.52

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Call a POISON CENTRE or doctor/physician if exposed or you feel unwell. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	 Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	 Obtain medical attention. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	 Harmful if swallowed. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if swallowed. Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnia, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

SAFETY DATA SHEET

Page: 4

Revision Date: 05/21/2015

Print Date: 6/29/2015 SDS Number: R0296766

Version: 1.0

	3D3 Nul
Zerex™ G-05 ANTIFREEZE COOLANT	
[™] Trademark, Ashland or its subsidiaries, registered	
in various countries	
857949	

	stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Cough pain in the abdomen and lower back cyanosis (causes blue coloring of the skin and nails from lack of oxygen) lung edema (fluid buildup in the lung tissue) acute kidney failure (sudden slowing or stopping of urine production) Convulsions
Notes to physician :	This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the baseited. Expressively, in an effective

hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	se extinguishing measures that are appro rcumstances and the surrounding enviror ater spray cam arbon dioxide (CO2) ry chemical	•
Unsuitable extinguishing media	igh volume water jet	
Specific hazards during firefighting	o not allow run-off from fire fighting to ent ourses.	er drains or water
Hazardous combustion products	cohols dehydes arbon dioxide and carbon monoxide hers xic fumes ydrocarbons odium oxides	
Specific extinguishing methods	roduct is compatible with standard fire-fig	hting agents.

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

Further information	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	:	Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
Conditions for safe storage	 Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

<u> </u>				D'.
Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ETHYLENE GLYCOL	107-21-1	Ceiling	100 mg/m3	ACGIH
			Aerosol.	
		TWA	10 mg/m3	ACGIHLIS_P
			Inhalable fraction	
			and vapor	
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	WEEL
DISODIUM TETRABORATE	1330-43-4	REL	1 mg/m3	NIOSH/GUID
ANHYDROUS			-	E
		TWA	10 mg/m3	TN OEL
		TWA	2 mg/m3	ACGIH
			Inhalable fraction.	
		STEL	6 mg/m3	ACGIH
			Inhalable fraction.	
Engineering measures	ventilation to applicable) o	 Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects. 		
Personal protective equipme	nt			
Respiratory protection	: A NIOSH-ap	proved air-purify	ing respirator with an	appropriate

Respiratory protection	A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air- purifying respirators is limited. Use a positive pressure, air- supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.
Hand protection Remarks	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	Not required under normal conditions of use. Wear splash- proof safety goggles if material could be misted or splashed into eyes.
Skin and body protection	Wear as appropriate: impervious clothing Safety shoes Choose body protection according to the amount and

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

concentration of the dangerous substance at the work place. Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures	: Wash hands before breaks and at the end of workday.
	When using do not eat or drink.
	When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liq	uid
Colour	: lig	ht yellow
Odour	: mi	ild
Odour Threshold	: No	o data available
рН	: Av	verage 6.5
	: No	o data available
Boiling point/boiling range		80 °F / 166 °C 1013 hPa)
Flash point		250.0 °F / > 121.1 °C ethod: Closed Cup
Evaporation rate	: > ´ Etl	1 hyl Ether
Flammability (solid, gas)	: No	o data available
Upper explosion limit	: 15	5.3 %(V)
Lower explosion limit	: 3.2	2 %(V)
Vapour pressure	: 1.1	1 mmHg (20 °C)
Relative vapour density	: >	1AIR=1
Relative density	: No	o data available
Density	: Av	verage 1.1362 g/cm3 (15.56 °C)
Solubility(ies) Water solubility		o data available
Solubility in other solvents	: No	o data available

ASHLAND.	Page: 8
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0
Partition coefficient: n- : No data available	

octanol/water	
Thermal decomposition	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat Exposure to moisture
Incompatible materials	 Acids Aldehydes Alkali metals Alkaline earth metals Bases iron salts strong alkalis Strong oxidizing agents Sulphur compounds
Hazardous decomposition products	Alcohols Aldehydes carbon dioxide and carbon monoxide ethers Hydrocarbons Organic acids Sodium oxides toxic fumes ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

ASHI A	
FETY DATA SHEET	Revision Date: 05/21/201
	Print Date: 6/29/201
	SDS Number: R0296760
ex™ G-05 ANTIFREEZE COC	
rademark, Ashland or its sub	sidiaries, registered
arious countries 949	
949	
	Skin contact
exposure	Skin contact Eye Contact
	Ingestion
Acute toxicity Harmful if swallowed.	
Product:	
Acute oral toxicity	:
	Remarks: Ingestion of medications contaminated with
	diethylene glycol has caused kidney failure and death in
	humans. Products containing diethylene glycol should be considered toxic by ingestion.
	considered toxic by ingestion.
Acute dermal toxicity	: Remarks: Skin absorption of this material (or a component)
	may be increased through injured skin.
Components:	
ETHYLENE GLYCOL:	
Acute oral toxicity	: LD 50 (Rat): 6,140 mg/kg
	LD50 (Human): Estimated 1.56 g/kg
	Assessment: The component/mixture is classified as acute
	oral toxicity, category 4.
Aguta inholation toxicity	· IC 50 (Bot): 10.0 mg/l
Acute inhalation toxicity	: LC 50 (Rat): 10.9 mg/l Exposure time: 1 h
	Test atmosphere: dust/mist
	Assessment: No adverse effect has been observed in acute
	inhalation toxicity tests.
Acute dermal toxicity	: LD 50 (Rabbit): 9,530 mg/kg
DIETHYLENE GLYCOL:	
Acute oral toxicity	: LD50 (Human): Expected 1,120 mg/kg
· · · · · · · · · · · · · · · · · · ·	Target Organs: Kidney
Acute inhalation toxicity	: LC50 (Rat): > 4.6 mg/l
, touto initialation toxicity	Exposure time: 4 h
	Test atmosphere: dust/mist
	Assessment: No adverse effect has been observed in acute
	inhalation toxicity tests.
Acute dermal toxicity	: LD 50 (Rabbit): 13,300 mg/kg
SODIUM BENZOATE:	
Acute oral toxicity	: LD 50 (Rat, male and female): 3,450 mg/kg
	\cdot

ASHLAND		
SAFETY DATA SHEET		

Page: 10

Revision Date: 05/21/2015

Print Date: 6/29/2015 SDS Number: R0296766

Version: 1.0

Zerex[™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949

DISODIUM TETRABORATE ANHYDROUS:

Acute inhalation toxicity	: LC50 (Rat): > 2.03 mg/l
	Exposure time: 4 h
	Test atmosphere: dust/mist
	Method: OECD Test Guideline 403
	Assessment: No adverse effect has been observed in acute
	inhalation toxicity tests.
	·

 Acute dermal toxicity
 : LD 50 (Rabbit): > 2,000 mg/kg

 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information. <u>Components:</u> ETHYLENE GLYCOL: Result: Mildly irritating to skin

DIETHYLENE GLYCOL: Species: Human Result: Slightly irritating to skin

SODIUM BENZOATE: Result: Mildly irritating to skin

DISODIUM TETRABORATE ANHYDROUS: Species: Rabbit Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

Components:

ETHYLENE GLYCOL: Result: Possibly irritating to eyes

DIETHYLENE GLYCOL: Species: Rabbit Result: Slightly irritating to eyes

SODIUM BENZOATE: Species: Rabbit Result: Irritating to eyes Method: OECD Test Guideline 405

DISODIUM TETRABORATE ANHYDROUS: Result: Slightly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Page: 11

Revision Date: 05/21/2015



Print Date: 6/29/2015

SDS Number: R0296766 Version: 1.0

Zerex[™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949

Components:

DIETHYLENE GLYCOL: Test Type: Maximisation Test (GPMT) Species: Guinea pig Method: Directive 67/548/EEC, Annex V, B.6. Result: Did not cause sensitisation on laboratory animals.

DISODIUM TETRABORATE ANHYDROUS: Test Type: Buehler Test Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information. <u>Components:</u> DIETHYLENE GLYCOL:

Genotoxicity in vitro	: Test Type: Ames test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative GLP: yes
	 Test species: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 479

Result: negative GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test Test species: Mouse Method: OECD Test Guideline 474 Result: negative GLP: yes

Carcinogenicity

 Not classified based on available information.

 Reproductive toxicity

 May damage fertility or the unborn child.

 Components:

 DISODIUM TETRABORATE ANHYDROUS:

 Reproductive toxicity

 :
 Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

 STOT - single exposure

Not classified based on available information. **STOT - repeated exposure** May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed. **Components:** ETHYLENE GLYCOL: Exposure routes: Ingestion Target Organs: Kidney, Liver

ASHLAND	Page: 12
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL: Exposure routes: Ingestion Target Organs: Kidney Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information. <u>Product:</u> No aspiration toxicity classification

Experience with human exposure

Components: DIETHYLENE GLYCOL: Liver Further information Product: Remarks: No data available

Carcinogenicity:

ouronrogeniony.	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity		
<u>Components:</u> ETHYLENE GLYCOL:		
Toxicity to fish	:	LC 50 (Bluegill (Lepomis macrochirus)): 27,540 mg/l Exposure time: 96 h Method: Static Remarks: Mortality
		LC 50 (Fathead minnow (Pimephales promelas)): 8,050 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l Exposure time: 48 h Test Type: static test

ASHLAND	Page: 13
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

DIETHYLENE GLYCOL: Toxicity to fish	:	LC 50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l Exposure time: 96 h Test Type: flow-through test
Toxicity to daphnia and other aquatic invertebrates	:	LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l Exposure time: 24 h Test Type: static test Method: DIN 38412
SODIUM BENZOATE:		
Toxicity to fish	:	LC 50 (Fathead minnow (Pimephales promelas)): > 100 mg/l Exposure time: 96 h Test Type: static test Method: Static Remarks: Mortality
Toxicity to daphnia and other aquatic invertebrates	:	LC 50 (Water flea (Daphnia magna)): > 100 mg/l Exposure time: 96 h Test Type: static test Method: Static Remarks: Mortality
DISODIUM TETRABORATE	٩N	HYDROUS:
Toxicity to fish		
	:	LC50 (Pimephales promelas (fathead minnow)): 79.7 mg/l Exposure time: 96 h Remarks: Information refers to the main component.
Toxicity to algae		Exposure time: 96 h
	:	Exposure time: 96 h Remarks: Information refers to the main component. NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201
Toxicity to algae Toxicity to fish (Chronic	:	Exposure time: 96 h Remarks: Information refers to the main component. NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 Remarks: Information refers to the main component. NOEC (Danio rerio (zebra fish)): 5.6 mg/l Exposure time: 34 d Test Type: semi-static test Method: OECD Test Guideline 210
Toxicity to algae Toxicity to fish (Chronic toxicity)	:	Exposure time: 96 h Remarks: Information refers to the main component. NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 Remarks: Information refers to the main component. NOEC (Danio rerio (zebra fish)): 5.6 mg/l Exposure time: 34 d Test Type: semi-static test Method: OECD Test Guideline 210

Biodegradability	: Result: Readily biodegradable Biodegradation: 70 - 80 %
	Exposure time: 28 d
	Method: OECD Test Guideline 301B

ASHLA	ND.	Page: 1 [,]
AFETY DATA SHEET		Revision Date: 05/21/201
		Print Date: 6/29/201
		SDS Number: R029676
ex™ G-05 ANTIFREEZE COOL Trademark, Ashland or its subsid various countries 7949		Version: 1.
SODIUM BENZOATE:		
Biodegradability	: Result: Readily Biodegradatior Exposure time Method: OECE	n: 88 %
DISODIUM TETRABORATE	ANHYDROUS:	
Biodegradability		ethods for determining biodegradability are not norganic substances.
Bioaccumulative potential		
Components: ETHYLENE GLYCOL: Bioaccumulation		1000 mg/l
Partition coefficient: n- octanol/water	: log Pow: -1.36	
DIETHYLENE GLYCOL: Bioaccumulation		scus idus (Golden orfe) on factor (BCF): 100
Partition coefficient: n- octanol/water	: log Pow: -1.47	
Mobility in soil		
<u>Components:</u> No data available		
Other adverse effects No data available		
Product:		
Additional ecological information		ntal hazard cannot be excluded in the event of handling or disposal., Harmful to aquatic life.
Components:		

SECTION 13. DISPOSAL CONSIDERATIONS

General advice : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.	Disposal methods	
	General advice	courses or the soil. Do not contaminate ponds, waterways or ditches with

ASHLAND.	Page: 15
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

ASHLAND	Page: 16
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

no

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	5314.69364

SARA 311/312 Hazards	:	Acute Health Hazard Chronic Health Hazard
SARA 313 Component(s)		ETHYLENE GLYCOL 107-21-1 94.07 %
California Prop 65		Proposition 65 warnings are not required for this product based on the results of a risk assessment.
The components of this proc TSCA		et are reported in the following inventories: On TSCA Inventory
DSL	:	All components of this product are on the Canadian DSL.
AUSTR	:	On the inventory, or in compliance with the inventory
ENCS	:	Not in compliance with the inventory
KECL	:	Not in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory

ASHLAND	Page: 17
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

IECSC

: On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/21/2015



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

- Causes serious eye irritation.
- H319 May damage fertility or the unborn child. H360
- May cause damage to organs through prolonged or repeated exposure H373 if swallowed.

Sources of key data used to compile the Safety Data Sheet Ashland internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the

ASHLAND	Page: 18
SAFETY DATA SHEET	Revision Date: 05/21/2015
	Print Date: 6/29/2015
	SDS Number: R0296766
Zerex [™] G-05 ANTIFREEZE COOLANT [™] Trademark, Ashland or its subsidiaries, registered in various countries 857949	Version: 1.0

information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System