



Castrol Activ 4T 20W-50

Continuous Protection

Description

Castrol Activ 4T 20W-50 with Actibond™ is modern, high quality engine oil developed specifically for 4-stroke motorcycle engines. The special Actibond™ clings and protects critical engine components, providing continuous protection in all riding conditions. Castrol Trizone Technology™ protects the engine, clutch and gears and allows the best functionality of these three critical areas of the motorcycle.

Application

Castrol Activ 4T 20W-50 is suitable for all 4-Stroke motorcycle engines where API SL (and below) and or JASO MA-2 and MA specifications are recommended.

Advantages

- Provides continuous protection even when the engine is off.
- Actibond™ molecules cling and protect during all riding conditions.
- Trizone Technology™ for protection of the engine, clutch and gears.
- Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	172
Viscosity Index	ASTM D2270	None	122
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	9000
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.7

Product Performance Claims

API SL
JASO MA-2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 4T 20W-50

07 Jul 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 4000093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com