



Hysol SL 35 XBB

High performance semi-synthetic metalworking fluid

Description

Castrol Hysol™ SL 35 XBB is a high performance semi-synthetic metalworking fluid which is boron, formaldehyde releasing agent and chlorine-free. It contains an additive package that provides excellent corrosion protection to machine tools and parts. It also provides excellent product stability which helps to lower the overall operational costs.

Hysol SL 35 XBB is suitable for large central systems and single sump machines.

Application

Hysol SL 35 XBB is especially designed for machining of cast iron and low-medium alloyed steel.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding	ü ü	ü ü	ü ü			
Milling, Turning (general machining)	ü ü	ü ü	ü			
Drilling	ü ü	ü ü				
Reaming, Tapping	ü ü	ü				
Broaching	ü ü	ü				

Advantages

- Extended fluid life can help to reduce maintenance and downtime
- Low foam in recommended water conditions (see details below)
- Excellent anti-corrosion properties to protect machine tools and parts
- Good wetting properties can help to reduce coolant drag out and help deliver cleaner machine tools and components
- Boron free to meet boron free waste requirements where applicable
- Chlorine, formaldehyde releasing agent and nitrite free which help you to fulfil aspects of legislative requirements and waste treatment requirements where applicable

Typical Characteristics

	Test Method	Unit	Value
Concentrate			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	35
Emulsion			
Appearance	Visual		Translucent - Milky
pH (4%)	DIN 51369 ASTM E70-97		9.6
Refractometer Factor			1.1

Recommended Concentrations

Grinding	4 - 6%
General Machining	6 - 10%
Drilling	6 - 8%
Reaming	6 - 10%
Broaching	6 - 10%
Water range	100-800 ppm CaCO ₃

Additional Information

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives				ü	

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer to the product safety data sheet.

Hysol SL 35 XBB
27 Feb 2015
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Limited, Industrial Lubricants & Services Rayala Towers , II Tower , V Floor 781-785 , Anna Salai , Chennai – 600 002
Tel: +91 44 42198899 / 823 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-42198885 Email: CustomerService.India@castrol.com
www.castrol.com/industrial