

Castrol Hysol XF

High performance semi-synthetic metalworking fluid

Description

Castrol Hysol™ XF is a high performance chlorine free semi-synthetic metalworking fluid. It contains a unique additive package that works in synergy to enhance machining performance and surface finish, provide excellent product stability, improve bio-resistance properties and lower the overall operations costs.

Hysol XF is suitable for large central systems and single sump machines.

Application

Hysol XF is especially designed for machining of steel. The product can also be used for machining of aluminium alloys and cast iron.

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding	✓✓	✓✓✓	✓✓✓	✓✓✓		✓
Milling, Turning (general machining)	✓✓	✓✓✓	✓✓✓	✓✓✓		✓
Drilling	✓✓	✓✓✓	✓✓✓	✓✓✓		✓
Reaming, Tapping	✓✓	✓✓✓	✓✓✓	✓✓		✓
Broaching	✓✓	✓✓✓	✓✓✓	✓✓		✓

Advantages

- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Low foam in recommended water conditions
- Good anti-corrosion properties to protect machine tools and parts
- Advanced lubricity compounds ensure improved tool life and part quality in steel and aluminium machining
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components
- Unique multi-functional product for multi-metal operations results in product consolidation

Typical Characteristics

	Unit	Test Method	Value
Concentrate			
Appearance		Visual	Amber
Mineral oil content	Wt%	Calculated	36
Emulsion			
Appearance		Visual	Milky
pH (5%)		DIN 51361 ASTM E70-97	9.3
Refractometer Factor			1.1

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	✓	✓	✓	✓	-

Recommended Concentrations

Grinding	5-6%
General Machining	5-7%
Drilling	5-8%
Reaming and tapping	6-10%
Broaching	8-10%
Water range	50-300 ppm CaCO ₃

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always.

For more details, please refer the product safety data sheet.

Castrol, Hysol, and the Castrol logo are trademarks of Castrol Limited, used under license

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.

Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019

www.castrol.com/industrial

Castrol Hysol XF
8 October 2008 Version 1