



Product Data

Castrol Rustilo 6302™

Neat Corrosion Preventive Oil

Description

These are specially selected lubricating oils, containing soluble anti-rust inhibitors, to offer high degree of corrosion prevention. These grades serve as lubricants as well as temporary protectives. Rustilo 6302 can be applied by dipping, spraying, roller coating, flowcoating, flushing or circulation, but the application surface must be cleaned and ried.

The protective film of these grades has lubricating properties and hence is not necessary to remove. However, if desired, the film can be removed by wiping.

Application

This is a heavier version of Rustilo 630 with a viscosity of SAE 30 range. It offers a protective lubricating film and is widely used for internal protection of gear boxes, hydraulic mechanism and external protection of instruments. On account of its high viscosity, it is popular for protection of cycle rims/frames, handle bars, etc.

Advantages

Product Feature	Operational Advantage	Customer Benefits
Oily film	Easy to apply and also to remove	Easy usability
Low Viscosity	Good finishing characteristics	Internal protection of Gearboxes an engines

Castrol Rustilo 6302
02.11.2006, Version Number 1.0

"Castrol Rustilo 6302" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com

www.castrol.com/industrial

Page 1 of 2



Product Data

Characteristics

Characteristics	Typical Value
Appearance	Amber, clear fluid
Specific gravity @ 30°C	0.888
Kin. Viscosity @ 40°C	100
Flash point °C PMCC	180
Coverage (Sq. mt./ltr.)	45-55
Film Thickness, Micron	10-12
Humidity Cabinet, Days	12 +
Salt Spray, Hrs	7 +
Protection - Indoors	6-7 months
Protection - Outdoors	1-2 months

The above data is typical and does not constitute a specification.

Castrol Rustilo 6302
02.11.2006, Version Number 1.0
"Castrol Rustilo 6302" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002.
Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019
Email:customer.service@castrol.com