

Castrol Superedge No.7™

Heavy Duty Emulsifiable Cutting Oil

Description

Castrol Superedge No.7 is a heavy-duty emulsifiable cutting oil. Superedge No. 7 owes its increased lubricating properties to the presence of Sulpho-Chlorinated additives. This product is specially designed for severe operations on difficult to machine materials where more expensive neat oils were used. This product is also recommended for general purpose light to medium duty pressing, stamping, wire and tube drawing operations.

Application

This product is suitable for all machining operations, including high speed grinding. Its value is shown particularly in arduous machining operations and where high degree of finish is required.

Recommended Dilutions

Operation	Mild & Low carbon steels	Low alloy steels	High alloy steels	Aluminium & alloys
Multi spindle automat operations	3.5%	5%	7%	4%
Gear roughing	5%	5%	10%	4%
Deep hole drilling	5%	5%	7%	5%
Broaching	5%	7%	10%	5%
High speed grinding	2.5%	2.5%	4%	2.5%

Advantages

Product Feature	Operational Advantage	Customer Benefit	
Sulpho - chlorinated EP additives	Good anti-chip welding properties hence can be used for heavy-duty operations.		
	Prevents wheel loading in grinding of 'stingy' metals like stainless steel and other alloys		
Anti-bacterial and anti-rust properties	Longer emulsion life. No corrosion problem.	Economy in use. Less rejections	
Ferrous and non-ferrous can be machined	Variety of operations over a wide range of materials can be done	Rationalisation of products used	

Castrol Superedge No.7

08.09.2006, Version Number 1.0

"Castrol Superedge No.7" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002. Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019 Email:customer.service@castrol.com

www.castrol.com/industrial Page 1 of 2



Product Data

Characteristics

Characteristics	Typical Value
Appearance	Clear & Homogenous
Emulsion Type	Brown Translucent
Emulsion Stability	
5%v/v Emulsion in Tap water	Stable for 24hrs
5%v/v Emulsion 250HW	Stable for 24hrs
5%v/v Emulsion 500HW	Stable for 24hrs
pH Value, 5 % in Dist Water	9.0
Cast Iron Corrosion	0/0-0

The above are typical figures and do not constitute a specification.

Castrol Superedge No.7 08.09.2006, Version Number 1.0 "Castrol Superedge No.7" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002. Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019 Email:customer.service@castrol.com

www.castrol.com/industrial Page 2 of 2