

# Castrol Texspin EE 10™

Energy Efficient Spindle Oil

## **Description**

Castrol Texspin oils are energy efficient premium lubricants specially designed and developed to meet the spindle lubrication requirement in Textile Industry. It has been formulated from highly solvent refined base stock possessing excellent chemical and oxidation stability and fortified with selected anti-oxidant, anti-wear, anti-foam and anti-rust additives.

### Application

Castrol Texspin oils are strongly recommended for lubrication of high speed textile spindles and machine tool spindle bearings. Castrol Texspin oils are also recommended for lubrication of special Industrial equipments e.g.

- ♦ Positive displacement blowers
- Timing gears
- Centrifugal separators
- ♦ Hydraulic systems of high precision tools

#### **Performance Level**

Meets the performance level of DIN 51524 (Part II)

## **Advantages**

Product Features	Operational Advantages	Benefits
High anti-wear performance	Reduced wear of Components  Downtime	Higher productivity due to reduced
Excellent resistance to oxidation	Reduced oil thickening	Extended oil life
High resistance to rust & corrosion	Reduced equipment Ageing	Extended equipment life

Castrol Texspin EE 10 11.11.2006, Version Number 1.0

"Castrol Texspin EE 10" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002. Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019 Email:customer.service@castrol.com



# **Product Data**

### **Characteristics**

Characteristics	Typical Value
Appearance	Bright Clear Yellow Liquid
Colour	1
Flash Point, COC, °C	170
K.Viscosity @ 40°C	12.5
Pour Point, °C	- 12

These are typical figures and do not constitute a specification.

Castrol Texspin EE 10 11.11.2006, Version Number 1.0

"Castrol Texspin EE 10" and Castrol are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information included in this publication is accurate as of the date of printing. However, such information may nevertheless be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol India Limited products. MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product

Castrol India Limited, Industrial Lubricants & Services, Rayala Towers, II Tower, V Floor, 781-785, Anna Salai, Chennai – 600 002. Tel: +91 44 42198899 Fax: +91 44 28416305 Toll Free: 1800 - 425 - 4588 (BSNL) Help Line: 044-39019019 Email:customer.service@castrol.com