



Gulf ATF PC

Automatic Transmission Fluid

Product Description

Gulf ATF PC is high quality transmission fluid specifically developed for use in many passenger car & heavy duty automatic transmissions, power steering and hydraulic fluid applications. It offers very good wear protection, thermo-oxidative stability, shear stability and frictional properties.

Features & Benefits

- High thermo-oxidative stability protects against deposits & oil thickening extending the life of components and oil.
- Enhanced friction characteristics and wear protection provide reliable, smooth & trouble-free operation.
- Special viscosity modifier ensures stay in grade viscosity during prolonged operation.
- An excellent anti-foam characteristic of fluid ensures proper lubrication all the time.
- Proven field performance ensures trouble free running.

Applications

- Passenger car and heavy duty automatic transmissions where fluids of such quality are recommended.
- Power steering units,
- Hydraulic power systems.
- Suitable for use in applications where Allison C-4 & Dexron IID type of fluids are recommended.

Suitable for Use Applications & Typical Properties:

Meets the following Specifications		
General Motors DEXRON® IID, Ford MERCON®		x
ZF TE-ML 03D, 04D, 05L, 09, 11A, 14A, 17C		x
Allison C-4, CAT TO-2, Volvo 97335, VOITH H55.6335.XX		x
MB 236.6, MAN 339 Type Z1, V1		x
Has the following Approvals		
ZF TE-ML 04D, 14A		x
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	7.8
Viscosity Index	D 2270	169
Brookfield Viscosity @ -40 °C, cP	D 2983	46600
Flash Point, °C	D 92	194
Pour Point, °C	D 97	-45
Density @ 15°C, kg/l	D 1298	0.8751

DEXRON® is a registered trademark of General Motors Corporation.

MERCON® is a registered trademark of Ford Motor Company

June 2013

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com