



Gulf CNG Supreme

Light-duty gas engine oil for mobile application

Product Description

Gulf CNG Supreme series are gas engine oils intended for use in light-duty vehicles running on Compressed Natural Gas (CNG), Liquefied Petroleum Gas (LPG) or propane. It is formulated from selected additives to provide superior detergency and dispersancy, oxidation and nitration resistance and protection against engine wear and corrosion. It exceeds the performance requirements of API SF/CD.

Features & Benefits

- Good oxidation and nitration resistance minimises sludge build-up and deposits
- Effective detergency and dispersancy keeps engines cleaner
- Provides superior protection against engine wear
- Controls combustion chamber carbon and ash deposits
- Provides protection against corrosion

Applications

- Light-duty vehicles running on CNG, LPG or propane and operating under moderate service conditions
- Other spark ignited gas engines where API SF/CD quality oils are specified

Specifications, Approvals & Typical Properties

SAE Viscosity Grade		10W-30	10W-40	15W-40	20W-50
Meets the following Specifications					
API SF/CD		X	X	X	X
Typical Properties					
Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	11.1	14.2	14.1	18.5
Viscosity Index	D 2270	135	140	138	124
Flash Point, °C	D 92	216	220	235	238
Pour Point, °C	D 97	-33	-33	-27	-24
Density @ 15°C, Kg/l	D 1298	0.879	0.880	0.884	0.869
Sulphated Ash, %wt	D 874	0.83	0.83	0.83	0.8
TBN, mg KOH/g	D 2896	5.97	5.97	5.97	5.4

March 2013

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com