



Gulf Gear ST

Extra High Performance Automotive Gear and Axle Oil

Product Description

Gulf Gear ST is thermally stable total driveline gear lubricant designed to meet the severe requirements of gearboxes and axle gears of Scania Vehicles. It is blended from selected high quality base oils and advanced performance additives to provide exceptional protection against thermal degradation, component wear and oil seal deterioration for extended service life. It possesses exceptional load-carrying capability to provide reliable lubrication in applications encountering extreme pressure and shock loading. It also offers effective protection against oxidation degradation and rust & corrosion. It approved against Scania STO 1:0 for both Gearbox and Axle Gears and also exceeds the requirements of API GL-5/MT-1, MIL-PRF-2105E, SAE J 2360 & various global equipment manufacturers.

Features & Benefits

- Exceptional load-carrying capability protects against wear in different operating conditions, enhances equipment durability and reduces maintenance costs
- Outstanding thermo-oxidative stability minimises deposits to provide longer gear, bearing and seal life and extended drain intervals
- Excellent rust and corrosion protection leads to reduced wear and longer component life
- Effective low temperature fluidity reduces wear and provides easy start-up under low ambient temperatures
- Good anti-foam properties ensure film strength for effective lubrication
- Excellent seal compatibility helps minimise leakages and reduce chances of contamination

Applications

- Gearboxes and Axle gears of Scania Trucks, Buses & coaches requiring oils approved against Scania STO 1:0
- On-road and Off-highway transmission applications requiring lubricants meeting any of the following specifications:
 - API GL-5/ MT-1
 - SAE J2360
 - MIL-PRF-2105E
- Not recommended for automatic transmissions and limited-slip differentials

Specifications, Approvals & Typical Properties

Meets the following Specifications		85W-140	80W-90
API GL-5, API MT-1, MIL-PRF-2105E, SAE J 2360,		X	X
MAN 342 Type M2, MACK GO-J, Scania STO 1:0		X	X
ZF TE-ML-05A, 07A, 12E, 16C, 16D, 17B,		X	X
Arvin Meritor 076		X	X
Has the following Approvals			
Scania STO 1:0 (Gearbox and Axle Gears)		X	
Approval by PRI (SAE J2360 qualified product)			X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity at 100 °C, cSt	D 445	26.3	14.4
Viscosity Index	D 2270	96	102
Flash Point, °C	D 92	220	219
Pour Point, °C	D 97	-18	-27
Density @ 15°C, kg/l	D 1298	0.905	0.8922

October 2012

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com