

Gulf Multi GT Passenger Car Motor Oil

Product Description

Gulf Multi GT is high quality passenger car motor oil designed for older turbocharged and naturally aspirated gasoline powered passenger cars and diesel powered light duty vehicles. It is blended using selected premium quality base oils and performance additives to provide excellent engine protection. It is developed to exceed the performance requirements of API (American Petroleum Institute) SG/CD and is available in three viscosity grades viz. SAE 10W-30, SAE 15W-40 & SAE 20W-50.

Features & Benefits

- Better thermo-oxidative stability minimises deposits & sludge build-up
- Effective rust inhibitors retard formation of rust in critical engine parts
- Better antiwear technology minimises engine wear to reduce maintenance costs
- Good Stay-in-grade performance ensures reliable lubrication even at higher load & operating temperatures

Applications

- Recommended for use in all modern high performance turbocharged & naturally aspirated gasoline powered passenger cars and diesel powered light duty vehicles requiring API SG & API CD quality oils
- It may also be used in older vehicles where an API service category SF or commercial category CC quality oil is recommended

Specifications, Approvals & Typical Properties

Specifications		10W-30	15W-40	20W-50
API SG		Х	X	X
API CD		Х	X	X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	10.90	14.30	18.30
Viscosity Index	D 2270	140	138	123
Flash Point, ^o C	D 92	226	220	234
Pour Point, ºC	D 97	-33	-27	-24
TBN, mg KOH/g	D 2896	5.70	5.70	5.70
Density @ 15ºC, Kg/l	D 1298	0.898	0.899	0.899
Sulphated Ash, %wt	D 874	0.68	0.68	0.68