



PRODUCT DATA SHEET

GulfSea Synth Gear Oil Series

Marine Synthetic Gear Oil specially formulated for all types of gears and bearings with higher oxidation resistance, hydrolysis resistance and anti-rusting properties.

Product Description

GulfSea Synth Gear Oil series are premium quality synthetic heavy duty industrial gear oils offering outstanding lubrication performance and load carrying capacity under severe operating conditions including shock loading. These are formulated from Polyalphaolefin (PAO) synthetic base stocks having exceptional oxidation resistance and thermal properties and excellent low temperature fluidity. The combination of naturally high viscosity index base stocks coupled with carefully selected additive technology provides excellent protection against scuffing and resistance against micro pitting fatigue under wide operating temperature range.

Features & Benefits

- Outstanding load carrying capability (micro-pitting) performance protects gears against scuffing and wear leading to enhanced equipment life and reduced maintenance costs.
- High viscosity index base stocks provide excellent low temperature fluidity and effective lubrication over a wide temperature range.
- Superior thermo-oxidative stability provides enhanced system cleanliness and enables longer service intervals.
- Low traction and enhanced lubricity helps provide extra energy efficiency.
- Excellent resistance to rust and corrosion protection and good demulsibility ensures trouble free operation at high temperatures and applications encountering water contamination.
- Good seal and paint compatibility with a wide variety of seals and paints.
- Performance meeting / exceeding the following requirements:
 - AISI 224
 - AGMA 9005-E02
 - DIN 51517 Part 3 _ group CLP
 - ISO 6743-6 _ category CKD
 - CINCINNATI MILACRON
 - DAVID BROWN

Applications

- Heavy-duty marine enclosed gears such as bow thruster and purifier.
- Industrial enclosed gear boxes operating under severe conditions like high load, extreme temperatures and wide temperature ranges.
- Filled for life systems.
- Bearing and circulation systems where high temperatures are encountered.
- Severe heavy duty gearboxes with high risk of micro pitting wear.



Marine

PRODUCT DATA SHEET

Typical Properties

GulfSea Synth Gear Oil Series			
		220	320
ISO Viscosity grades		220	320
Typical Properties			
Test Parameters	ASTM Method	Test Values	
Viscosity @ 40 °C, cSt	ISO 3104 (D 445)	220.1	313.8
Viscosity Index	ISO 2909 (D 2270)	152	155
Pour Point, °C	ISO 3016 (D 97)	-36	-30
Density @ 15°C, kg/m ³	ISO 3675	859.7	861.7
Flash Point, °C	ISO 2592 (D 92)	237	233
FZG Micropitting	FVA 54 IIV	10+	10+
FZG A/8.3/90	DIN 51 354/2	>13	>13

July 2014