

MAK AUTO XL

Description

A premium Diesel Engine oil for lubrication of 4 stroke Auto Rickshaws running on Diesel. This oil is formulated using severely hydro-processed base oils and appropriate additive chemistry.

Application

Suitable for PIAGGIO & MAHINDRA 4 stroke Auto Rickshaws running on Diesel under normal operating conditions.

Benefits

- Keep engine components clean
- Provide excellent protection from wear, corrosion and deposits
- Enhanced oxidation stability ensures reduced oil thickening and extends engine & oil life
- Being Multi grade oils, these are suitable for use in all seasons

Performance Level

- API CF-4

Technical Specifications

Characteristics	ASTM TEST METHOD	MAK AUTO EXCEL 15W-40
K.V.@100 deg C, cSt	D-445	14.3
Viscosity Index	D-2270	137
Flash Point(COC), deg C	D-92	224
Pour Point, deg C	D-97	-24

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.

'A' Installation, Sewree Fort Road, Sewree (East)

Mumbai -400015

E-mail: MAKcustomercare2@bharatpetroleum.in

Tel No.: 022-24176351