

## **MAK AUTRAN III**

### **Description**

Premium quality transmission and power steering oil blended with superior quality hydro finished base oils & appropriate additives. It ensures smooth working of automatic transmissions or torque converters, power steering systems And hydraulic systems of automobiles

### **Application**

It is recommended for Automatic Transmissions / torque converters of latest Generation passenger cars, Power Steering and hydraulic fluid applications in passenger cars & commercial vehicles requiring DEXRON III fluid

### **Benefits**

- Good anti-wear and anti-corrosion properties giving good protection to automatic transmission /power steering system component
- Outstanding low temperature fluidity ensures trouble free year-round operation
- Better seal compatibility increases the service life of seal components
- Excellent oxidation & thermal stability which extends the oil life
- Ensures smooth operation with a minimum power loss

### **PERFORMANCE LEVEL**

- Dexron III of General Motors

## Technical Specifications

Characteristics	ASTM	MAK AUTRAN III
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Brown
Density @15°C, gm/ml	D1298	0.861
K.V at 100° C, cSt	D445	7.61
Copper Corrosion @ 100° C for 3hrs	D130	1b
Flash Point, (COC), ° C	D92	215
Foaming Stability @ 93.5 °C Qty. of foam in ml	D 892	Nil / Nil

All the mentioned values are typical which may vary from batch to batch.

## Storage and Handling

- Indoor Storage is always preferable
- Closed Barrels should be kept horizontally with bung position at 3'O Clock - 9 'O Clock position
- Barrels should be kept away from dusty or heated areas as much as possible
- During handling any contact with dust must be avoided

## Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

## Advice

For any further advice on applications or otherwise please contact the nearest Bharat Petroleum Territory Office or Technical Services Department at the address given below.

### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.

BPCL 'A' Installation, Sewree Fort Road, Sewree (East)

Mumbai -400015

E-mail: [MAKcustomer care2@bharatpetroleum.in](mailto:MAKcustomer care2@bharatpetroleum.in)

Tel No.: 022-24176351