

MAK D GEN XP

Description

MAK D GEN XP is exclusively formulated premium quality multi grade Diesel Engine Oil designed for providing complete protection to modern, highly rated, turbo-charged stationary DG sets used for powering mobile towers working under moderate to severe operating conditions.

Application

MAK D GEN XP is recommended for naturally aspirated / turbo-charged stationary DG sets used for powering mobile towers.

Benefits

- This oil is expected to provide around 40% more wear protection of the engine components under normal running conditions.
- The superior detergency–dispersancy chemistry of the oil ensures extra engine cleanliness
- This oil, due to its excellent soot handling capacities and resistance to oxidation, has the potential to extend the oil drain period by 50% under normal operating conditions besides enabling longer oil filter life
- Being Multi grade oils, these are suitable for use in all seasons

Performance Level

- API CH-4
- MB 228.3

Technical Specifications

Characteristics	ASTM TEST METHOD	MAK D GEN XP
Appearance	-	Clear & Bright
Colour, Visual	-	Brown
Density @ 15 deg C	D-1296	0.8885
K.V.@100 deg C, cSt	D-445	14.20
Viscosity Index	D-2270	145
Flash Point(COC), deg C	D-92	232
Pour Point, deg C	D-97	-24
Copper Corrosion @ 100 deg C for 3 Hrs.	D-130	1a

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351