

MAK FREEZOL CS

Description

These are highly refined specially treated straight mineral, paraffinic oils designed for moderate applications

Application

MAK Freezol CS is recommended for use in any application where temperatures go upto -10 ° C

Benefits

- Good oxidation stability
- High viscosity index

Performance Level

- Proprietary grade

Technical Specifications

Characteristics	ASTM	MAK FREEZOL CS
		68
Appearance	--	Bright & Clear fluid
Density at 15°C	D1298	0.875
K.V at 40° C, cSt	D445	68.5
Viscosity Index	D2270	0.002
Pour Point, °C	D97	-24
Flash Point, (COC), °C	D92	230
Copper Strip Corrosion Test at 100°C for 3 hrs.	D130	1a
Acidity		
a) total, mg KOH / g		0.03
b) Inorganic		Nil

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Distributor

INTERSTATE SUPPLY COMPANY

51, Bhupen Bose Avenue, Kolkata-700004, India

Phone: +91 (033) 2555 5651/9554 FAX: +91 (033) 2533 7211

E-mail: info@bpckolkata.com