

MAK GOLD PLUS

Description

These are heavy duty oils formulated from highly refined base oils and detergent-dispersant inhibitors, anti-wear additives and a special oil thickening control agent.

Application

This oil is recommended for high speed Naturally Aspirated / Turbo / Supercharged diesel engines operating at low speed and high torque conditions prevalent in prolonged city stop & go driving conditions and also in hilly regions.

It is also recommended for use in Heavy Duty Commercial Vehicles, Light Commercial Vehicles and Multi Utility Vehicles.

Benefits

- Excellent viscosity control under extreme operating conditions.
- Improved engine cleanliness.
- Extended oil drain interval.
- Reduced oil consumption.
- Longer engine life.
- Suitable for use in all seasons.

PERFORMANCE LEVEL

- API CF
- MACK T-7 / T-8A Test
- IS 13656: 2002 Type EDL3
- US MIL-L-2104C

Technical Specifications

Characteristics	ASTM	MAK GOLD PLUS
		20W40
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C, gm/ml	D1298	0.8894
K.V at 100° C, cSt	D445	14.50
Copper Corrosion @ 100° C for 3 hrs	D2270	1a
Flash Point, (COC), °C	D97	236
Viscosity Index	D92	108
Pour Point, °C	D130	-21
Foaming Tendency / Stability: Qty. of foam in ml a) Sequence I b) Sequence II c) Sequence III	D892	Nil / Nil 10 / Nil Nil / Nil

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
 Mumbai -400015
 E-mail: MAKcustomercare2@bharatpetroleum.in
 Tel No.: 022-24176351