

MAK MATSYA 2T

This is semi-synthetic, low smoke environmentally friendly oil for 2-stroke engines. Blended from highly refined mineral base oil and synthetic component fortified with finely balanced low ash additives. A high quality diluent is added to ensure instantaneous self-mixing of oil with fuel.

It is recommended for 2-stroke engines fitted in outboard boats like Yamaha, Suzuki etc.

- Extremely low visible exhaust smoke levels.
- Reduced spark plug fouling and silencer deposits.

- JASO FC
- API TC
- ISO GC

Characteristics	ASTM	MAK MATSYA 2T
Appearance		Clear & Bright
Colour, Visual Observation	--	Green
Density @15°C	D1298	0.9010
K.V at 100° C, cSt	D445	9.3
Copper Corrosion @ 100° C for 3 hrs	D130	1a
Flash Point, (COC), °C	D2270	96

All the mentioned values are typical which may vary from batch to batch.

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351