

MAK REDI KOOL

Description

MAK REDI KOOL is specially formulated synthetic, environment friendly radiator coolant. It is a high performance coolant designed to provide efficient protection from winter freezing and summer over heating. It is a ready to use product.

Application

MAK REDI KOOL is recommended for use in passenger cars, light commercial vehicles, heavy Vehicles and heavy earth moving equipment as a radiator coolant without dilution with water in closed loop coolant circulation systems.

Benefits

- Dissipates heat efficiently
- Prevents coolant freeze-up and boil over
- Protects radiator and engine block from rust & corrosion
- Reduces maintenance cost of radiator

Performance Level

- JIS K 2234-1994, Class II (LLC Type)
- IS 5759:2006

Technical Specifications

Characteristics	ASTM Test method	MAK REDI KOOL
Colour	-	Dark green
Density @20°C, gm/ml	D-1296	1.062
Boiling point, ° C	D-1120	108
pH	D-1287	8.04
Water Content, % wt	D-95	70.2

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351