



MAK[®]
LUBRICANTS

MAK SHOCK ABSORBER FLUID

This is specially formulated to meet the severe lubrication requirements of latest design automotive shock absorbers.

This oil is recommended for use in latest design automotive shock absorbers.

These are approved by M/s Munjal Showa Ltd.

- Ensures smoother ride by excellent dampening of shock loads
- Provides very high degree of chemical stability
- Good seal compatibility
- very low pour point which will enable its use over wide temperature range

- Proprietary brand

Characteristics	ASTM	MAK SHOCK ABSORBER OIL
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Red
Density @15°C	D1298	0.9010
K.V at 40° C, cSt	D445	35.5
Viscosity Index	D2270	106
Flash Point, (COC), °C	D92	186
Pour Point, °C	D97	-42
Aniline point, °C	D611	82.7
Foaming Tendency / Stability: Qty. of foam in ml a) Sequence I b) Sequence II c) Sequence III	D892	10 / Nil 10 / Nil 10 / Nil

All the mentioned values are typical which may vary from batch to batch.

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
 BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
 Mumbai -400015
 E-mail: MAKcustomercare2@bharatpetroleum.in
 Tel No.: 022-24176351