

# **MAK SPIROL XHD**

# **Description**

These are long life heavy duty gear oils meant for gears, particularly hypoid gears, in axles operating under various combinations of high-speed shock loads and low-speed, high-torque conditions. These are designed to extend the life of oil and components. These oils can withstand bulk oil temperatures as high as 150°C.

# **Application**

- It is recommended for hypoid / bevel gears in rear axles of the vehicles operating under severe service conditions. It can also be used in gear boxes wherever OEMs recommend GL-5 type Oils.
- MAK Spirol XHD 90 grade is approved by M/S Balmier Chrysler for use in Mercedes-Benz vehicles & assemblies as specified in their sheet 235.0

#### **Benefits**

- Designed for heavy duty operations
- This oil can withstand bulk oil temperatures as high as 150°C
- This is designed to extend the life of oil and components

#### **Performance Level**

- API GL-5
- IS 1118:1992 (EP Type GL-5)
- US MIL-L-2105D



## **Technical Specifications**

Characteristics	ASTM TEST METHOD	MAK SPIROL XHD 90	MKA SPIROL XHD 85W140
Appearance	-	Clear & bright	Clear & bright
Colour, Visual	-	Brown	Brown
K.V.@100 deg C, cSt	D-445	16.8	26.4
Viscosity Index	D-2270	98	95
Flash Point(COC), deg C	D-92	198	224
Pour Point, deg C	D-97	-9	-15

All the mentioned values are typical which may vary from batch to batch.

### Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

#### **Health & Safety**

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

#### **Advice**

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

#### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.

BPCL 'A' Installation, Sewree Fort Road, Sewree (East)

Mumbai -400015

E-mail: MAKcustomercare2@bharatpetroleum.in

Tel No.: 022-24176351