



Mobil Super 1000 MS 15W-40

Premium Multigrade Passenger Vehicle Engine Oil

Product Description

The Mobil Super 1000 MS 15W-40 is a premium mineral motor oil designed to provide a high level of performance and protection under most operating conditions. Mobil Super 1000 MS 15W-40 is primarily intended for use in Maruti Suzuki Diesel Passenger Cars.

Features and Benefits

Mobil Super 1000 MS 15W-40 provides very good engine protection and helps extend engine life.

- Excellent wear protection
- Excellent engine cleanliness

Specifications and Approvals

| Mobil Super 1000 MS 15W-40 meets or exceeds the requirements of : | |
|---|---------------|
| | 15W-40 |
| API SJ | X |
| Mobil Super 1000 MS 15W-40 is recommended by ExxonMobil for use in applications requiring: | |
| | 15W-40 |
| API CG-4/CF-4/CF | X |

Typical Properties

| Mobil Super 1000 MS 15W-40 | |
|-----------------------------------|--------|
| SAE Grade | 15W-40 |
| Viscosity, ASTM D 445 | |
| cSt @ 40°C | 106 |
| cSt @ 100°C | 14.4 |
| Viscosity Index, ASTM D 2270 | 139 |
| Pour Point, °C, ASTM D 97 | -27 |
| Flash Point, °C, ASTM D 92 | 220 |
| Density @ 15 °C, kg/l, ASTM D4052 | 0.88 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product,

take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

9-2010

ExxonMobil Lubricants Private Limited

4th Floor Building 10, Tower C, DLF Cyber City, Gurgaon, Haryana 122002 India

+91 124 6581 601

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2015 Exxon Mobil Corporation. All rights reserved.