



ISO 21469 Certified

## FOODLUBE® Seamer Fluid 150

High performance, food grade fluid for can seamers  
Viscosity grade: ISO VG 150

### Product Overview

ROCOL® FOODLUBE Seamer Fluid 150 is a non-toxic can seamer lubricant which is supplied with a viscosity grade of ISO VG 150.

ROCOL FOODLUBE Seamer Fluid 150 is designed specifically for the lubrication of can seamers operating with either total loss or recirculating lubrication systems.

ROCOL FOODLUBE Seamer Fluid 150 is a tenacious, extreme pressure (EP), synthetic oil containing additives to boost performance, improve adhesion and provide excellent corrosion protection.

It is ideal for use in food, pharmaceutical and other clean environments where NSF H1 lubricants are required.

### Features and Benefits

- FOODLUBE Seamer Fluid 150 offers excellent wide temperature resistance of -20°C to +150°C.
- FOODLUBE Seamer Fluid 150 has outstanding EP performance.
- FOODLUBE Seamer Fluid 150 provides a tenacious, EP film with excellent water wash-off resistance and corrosion protection.
- FOODLUBE Seamer Fluid 150 has excellent stability resulting in extended relubrication intervals and a reduction in lubricant usage.

### Directions for Storage and Use

- For optimum performance drain & flush prior to filling with ROCOL FOODLUBE Seamer Fluid 150.
- When using FOODLUBE Seamer Fluid 150 in a recirculating system ensure that the oil filters are renewed during an oil change.
- The storage temperature of ROCOL FOODLUBE Seamer Fluid 150 should be controlled between +1°C and +40°C.
- Shelf life is 3 years from date of manufacture.

### Specifications

- FOODLUBE Seamer Fluid 150 does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FOODLUBE Seamer Fluid 150 is manufactured from only FDA listed ingredients:
  - FDA Group 21 CFR 178.3570
- FOODLUBE Seamer Fluid 150 is NSF registered:
  - FOODLUBE Seamer Fluid 150 – 143579
- ISO 21469 certified

### Pack Sizes

Pack Size	Part Code
20L	16025
200L	16029





ISO 21469 Certified

## FOODLUBE® Seamer Fluid 150

High performance, food grade fluid for can seamers  
Viscosity grade: ISO VG 150

Property	Test Method	Result
Appearance	Visual	Pale yellow, almost colourless, liquid
Base Type	N/A	Polyalphaolefin
Viscosity at 40°C	IP71 – ASTM D445	150cSt
Viscosity at 100°C	IP71 – ASTM D445	16.8cSt
Viscosity index	IP71 – ASTM D445	121
Temperature Range	N/A	-20°C to +150°C

Values quoted above are typical and do not constitute a specification.

### Safety Data Sheets

Safety data sheets are available for download from our website [www.rocol.com](http://www.rocol.com) or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 3 Date: 05-13

T +44 (0) 113 232 2600  
F +44 (0) 113 232 2740  
E [customer-service@rocol.com](mailto:customer-service@rocol.com)  
[www.rocol.com](http://www.rocol.com)

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67  
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001  
Certificate No. FM 12448



BS EN ISO 14001  
Certificate No. EMS 67596



OHSAS 18001  
Certificate No. OHS 78173



INVESTORS  
IN PEOPLE