

Tuflube Allweather

Water resistant adhesive lubricant for a range of applications

Product Overview

ROCOL® Tuflube Allweather is a versatile and highly adhesive lubricant designed for effective lubrication and protection in extremely wet and highly loaded environments.

Tuflube Allweather has been designed as a self-repairing lubricant for slides, plain bearings & open gears. Conventional lubricants are pushed off the rubbing areas whereas Tuflube Allweather repairs the film as the surfaces continue to rub together.

Tuflube Allweather is a highly adhesive, high load grease which can even be applied underwater. It will continue operating even when used in submerged or tidal flow conditions.

Features and Benefits

- ROCOL Tuflube Allweather has a wide temperature range of -30°C to +70°C.
- Outstanding EP performance with a weld load of 800kg.
- Tuflube Allweather is a tough, tenacious, self-repairing film which maintains a lubricant film on the surface longer than conventional lubricants.
- Excellent corrosion resistance to protect in humid, damp and even wet/submerged conditions.
- Tuflube Allweather can even be applied under water due to its excellent water displacing properties and resistance to water wash-off.
- Tuflube Allweather is easy to apply and free from bitumen and solvents.

Directions for Storage and Use

- Apply manually or with an applicator suitable for NLGI No. 1 grease.
- Do not mix with other lubricants as performance may be impaired.
- The storage temperature should be controlled between +1°C and +40°C.
- Shelf life is 3 years from date of manufacture.

Typical Applications

- ROCOL Tuflube Allweather is a soft pumpable grease for plain bushes, slides and open gears even when used outdoors in wet environments.
- It is ideal for sliding booms and open gears on cranes particularly those that have to be lubricated outdoors in all weather conditions.
- Tuflube Allweather has proven highly successful as a bucket pin lubricant for heavy plant and it remains pumpable even in cold conditions.
- Tuflube Allweather excels in applications such as lead screws, penstocks, sluice gates and winding gear on locks and in water treatment plants.

Pack Sizes

Pack Size	Part Code
400g cartridge	18271
5kg	18276
18kg	18244

Tuflube Allweather

Water resistant adhesive lubricant for a range of applications

Property	Test Method	Result
Appearance	Visual	Smooth, black grease
NLGI No.	IP 50 – ASTM D217	0/1
Base Type	N/A	Highly refined mineral oil
Base Fluid Viscosity at 40°C	IP 71	780cSt
Base Fluid Viscosity at 100°C	IP 71	42cSt
Thickener	N/A	Aluminium soap
Solids	N/A	Graphite
Temperature Range	N/A	-30°C to +70°C
4-Ball:		
Weld Load	IP 239 - ASTM D2596	800kg
Mean Hertz Load	IP 239 - ASTM D2596	107kg
Timken 'OK' Load	IP 326 – ASTM D2509	45 lbs
Salt Spray Corrosion Resistance	ASTM B-117	No corrosion (10 days)
Water Spray Off	ASTM D404	<0.5% loss

Values quoted above are typical and do not constitute a specification.

Safety Data Sheets

Safety data sheets are available for download from our website www.rocol.com or may be obtained from your usual ROCOL contact.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Issue: 1 Date: 01-11

T +44 (0) 113 232 2600
 F +44 (0) 113 232 2740
 E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of *ITW* Ltd



BS EN ISO 9001
 Certificate No. FM 12448



BS EN ISO 14001
 Certificate No. EMS 67596



OHSAS 18001
 Certificate No. OHS 78173



INVESTORS
 IN PEOPLE