


Shell PC 0943 5W-30

Factory Fill Engine Oil



Shell PC 0943 is a high quality engine oil blended for use in high-speed, naturally aspirated and turbocharged engines.

Applications

Initial fill of Gasoline engines

Performance Specifications

Nissan First Fill

API: SL

ILSAC: GF-3

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Oil drain intervals

The oil drain interval as specified by the engine manufacturer should be adhered to.

Health & Safety

Shell PC 0943 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Typical Physical Characteristics

Shell PC 0943	
SAE Grade	5W-30
Kinematic Viscosity @ 40°C cSt 100°C cSt (IP 71)	60.0 10.3
Viscosity Index (IP 226)	160
Density @ 15°C kg/l (IP 365)	0.861
Flash Point °C (COC) (IP 36)	226.0
Pour Point °C (IP 15)	-39.0

These characteristics are typical of current production. Variations in these characteristics may occur.