

# AZOLLA AF



LUBRICATION



**TOTAL**

## Premium Ashless Anti-Wear Hydraulic Oil.

### APPLICATIONS

#### Hydraulic systems.

- **AZOLLA AF** oils are premium anti-wear hydraulic fluids and lubricants. They are formulated from high quality paraffinic base stocks and a fully formulated, thermally stable, non-zinc additive package. They meet or exceed the requirements of the leading manufacturers of hydraulic equipment and are available in a wide range of viscosities from ISO 22 to ISO 68.
- **AZOLLA AF** oils have been specifically designed to be used in all types of hydraulic pumps and motors that require the use of anti-wear hydraulic oils. The appropriate viscosity grade will provide excellent service in plain and anti-friction bearings and moderate service in gear reducers.

### SPECIFICATIONS

#### International specifications.

- PARKER (Form. Denison) HF-0, HF-1, HF-2
- EATON 35VQ25
- Bosch Rexroth RE 90220
- ISO 6743/4 CATEGORY L-HM
- MAG (CINCINNATI MILACRON) P68, P69, P70
- DIN 51524 PART 2
- Conestega Pump Test ISO 20763

### ADVANTAGES

#### Long equipment life and high operating reliability.

- Ashless, zinc-free.
- Excellent anti-wear properties.
- Resistance to hydrolysis and oxidation.
- Inert towards metals (non-staining and no corrosive wear).
- Good compatibility with elastomers and seals.
- Excellent water/oil demulsification properties.
- Excellent anti-foaming, anti-corrosion, and anti-oxidation properties.

TYPICAL CHARACTERISTICS	METHODS	AZOLLA AF			
		22	32	46	68
Viscosity at 40°C, cSt	ASTM D 445	22.0	32.0	46.0	68.0
Viscosity Index	ASTM D 2270	> 95	> 95	> 95	> 95
Density @ 60°F, lbs./gal.	ASTM D 1298	7.24	7.25	7.28	7.32
Specific Gravity @ 60/60°F	ASTM D 1298	0.867	0.868	0.872	0.877
Flash Point, COC, °F	ASTM D 92	405	405	410	450
Copper Strip Corrosion	ASTM D 130	1A	1A	1A	1A

TOTAL Lubricants USA, Inc.

Linden, NJ 07036  
5 North Stiles Street  
908.862.9300/800.526.4127

Rockingham, NC 28379  
709 Airport Road  
800.323.3198 / 800.526.4127

Knoxville, TN 37914  
3315 Riverside Drive  
800.323.3198 / 800.526.4127