

# DEXRON VI ATF



## Licensed Dexron VI ATF for GM vehicles

### APPLICATIONS

#### Types of service

- **DEXRON VI ATF** is a high performance automatic transmission fluid designed to meet the requirements of the newest General Motors vehicles.
- **DEXRON VI ATF** is backward compatible with earlier versions of Dexron such as Dexron III. It may be used in hydraulic systems as a wide range hydraulic fluid or it may be used as a low to medium quality rotary air compressor fluid.

### PERFORMANCE

#### Transmission builders

General Motors

#### Vehicle approvals

General Motors Dexron VI, license J-60370

### CUSTOMER BENEFITS

#### High technical performance

- Exceptional cleanliness of delicate control valves resulting in trouble-free transmission performance.
- High viscosity index gives excellent performance over a wide temperature range.
- Proper frictional properties provide the required shift feel characteristics.
- Excellent anti-wear, anti-corrosion, anti-foam and oxidation resistance.
- Excellent low temperature fluidity protects against wear under extremely cold operating conditions.

### CHARACTERISTICS

| TYPICAL TEST PROPERTIES—DEXRON VI* ATF               |              |
|--|--------------|
| Specific gravity (lbs/gallon)                        | 0.844 (7.03) |
| Viscosity, cSt @ 40°C ASTM D-445                     | 28.7         |
| Viscosity, cSt @ 100°C ASTM D-445                    | 6.0          |
| Viscosity index ASTM D-2270                          | 152          |
| Brookfield viscosity, cP @ -40°C (-40°F) ASTM D-2983 | 12,030       |
| Pour point, °C (°F) ASTM D-97                        | -51 (-60)    |
| Flash point, °C (°F) ASTM D-92                       | 229 (445)    |
| Color, visual  | Red          |

DEXRON® is a registered trademark of General Motors Corporation.

## TOTAL Lubricants USA, Inc.

### DEXRON VI

Sheet updated: 11/25/2014

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.323.3198  
www.totallubricantsusa.com

TOTAL Lubricants USA has a policy of continuous improvement and reserves the right to change specifications as our technology progresses.  
We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites. Total-techspecs.com