


DRASTA 107 S



METALWORKING



TOTAL

Petroleum-Based, Fast Quenching Oil.

APPLICATIONS

- **DRASTA 107 S** is a premium grade, petroleum-based, fast quenching fluid formulated from specially selected basestocks and wetting agents. This product contributes the proper quenching properties to provide minimum distortion and maximum parts hardness.
- **DRASTA 107 S** contains a highly effective anti-oxidant designed to prolong quench fluid life by providing excellent resistance to oxidation.
- **DRASTA 107 S** is a high speed quench oil used for applications such as low hardenability alloys, carburized and carbo-nitrided components, or large cross-sections of medium hardenability steels where very high rates of cooling are required to ensure maximum mechanical properties.

ADVANTAGES

- Excellent resistance to oxidation.
- High thermal stability.
- Minimum distortion.
- Maximum parts hardness.
- High flash point.

TYPICAL CHARACTERISTICS	DRASTA 107 S
Appearance	Dark Opaque Liquid
Color, ASTM D-1500	8.0
Viscosity at 40°C, cSt	24.0 - 26.0
Density @ 60 °F, lbs./gal.	7.18
Specific Gravity @ 60/60 °F	0.862
Flash Point, COC, °F	385
Fire Point, COC, °F	415
Quench speed @ 77°F, sec.	10.0 - 13.0

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127