



# ELFMATIC G3 SYN

Synthetic based fluid for automatic transmissions and hydraulic systems

## USES

**Automatic  
gearboxes**

Recommended for all automatic transmissions and powershifts as well as hydraulic systems for which the manufacturer recommends a DEXRON® III :

- automatic gearboxes
- powershift transmissions
- hydraulic clutches
- power-assisted steering systems.

## PERFORMANCES

DEXRON® III

APPROVED BY  
MAJOR MANUFACTURERS

- Manufacturer approvals :
  - ALLISON C4
  - FORD MERCON®
  - Level DEXRON® III G
  - MAN 339 Type V-1
  - MAN 339 Type Z-2
  - MB-Approval 236.5
  - RENAULT DP0
  - VOITH H 55.633535
  - ZF TE-ML 14B, 16L

## CLIENTS BENEFITS

**Driving comfort without  
chatter**

**Longer lasting  
performances**

**Extended drain interval**

**Fuel saving**

- Exceptional thermal stability and oxidation resistance, preventing the formation of deposits in immersed clutches.
- Very high cold fluidity and enhanced lubricity permitting jolt-free operation of the box without excessive slip, at all temperatures and all speeds.
- Friction properties especially adapted for the coating materials on clutches, brakes and the lock-up systems installed in modern gearboxes.
- Excellent compatibility with the joints; enhanced anti-wear, anti-corrosion and anti-foaming performances.
- Perfect neutrality with non-ferrous metals (copper, etc...).
- Maintenance of the physico-chemical properties at their optimum level throughout the service life recommended by the manufacturer.

## CHARACTERISTICS

ELFMATIC G3 SYN	Unit	
Density at 15 °C	---	0.867
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	36
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	7.2
Viscosity index	---	169
Pour point	°C	-55

The characteristics shown are mean values

TOTAL LUBRIFIANTS

La Spazio Box C40

562 Av du Parc de l'île, 92029 Nanterre Cedex

1/1

ELFMATIC G3 SYN

Août 2010

N° MPR 09/07



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant