

LUBRILAM 6203 S



METALWORKING



TOTAL

Rolling Oil.

APPLICATIONS

- **LUBRILAM 6203 S** oil is a bright, clear, light viscosity rolling oil. It is non-staining to all metals and provides high thermal and oxidation stability.
- **LUBRILAM 6203 S** oil is compounded with lubricity agents, metal deactivators, and anti-oxidant additives which provide excellent cooling, good friction control for balanced "bite and slip" and good bearing protection.

LUBRILAM 6203 S is recommended for rolling on Zendzimir rolling mills of various metals.

ADVANTAGES

- High thermal and oxidation stability.
- Non-staining.
- Good compatibility with elastomers and seals.
- Low temperature properties.
- Low volatility.
- Extreme pressure protection.

TYPICAL CHARACTERISTICS	METHODS	LUBRILAM 6203 S
Appearance	Visual	Bright Clear Liquid
Color	ASTM D 1500	1.0
Viscosity at 40°C, cSt	ASTM D 445	10.5 - 13.5
Viscosity at 100°F, SUS	ASTM D 445	80
Viscosity Index	ASTM D 2270	>95
Density @ 60°F, lbs./gal.	ASTM D 1298	7.15
Specific Gravity @ 60/60°F	ASTM D 1298	0.859
Flash Point, COC, °F	ASTM D 92	385
Copper Strip Corrosion	ASTM D 130	1A

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127