

MOLDOL 208 S



DEMOLDING



TOTAL

Ceramic Casting Oil.

APPLICATIONS

- **MOLDOL 208 S** is a specialized lubricant designed to serve as a release agent during the casting of ceramic components. This product has been formulated to provide the proper wetting, lubricant film, and release properties during the release process.
- **MOLDOL 208 S** is generally applied through automatic spray systems in order to assure a consistent film. However, manual spraying or brush application may be acceptable.

ADVANTAGES

- Ensures good lubricant film.
- Promotes good surface finish.
- Mild odor.
- Excellent wetting ability.

TYPICAL CHARACTERISTICS	METHODS	MOLDOL 208 S
Appearance	Visual	Clear Amber Liquid
Color	ASTM D 1500	3.5
Viscosity at 40°C, cSt	ASTM D 445	8.0
Density @ 60 °F, lbs./gal.	ASTM D 1298	6.89
Specific Gravity @ 60/60 °F	ASTM D 1298	0.828
Flash Point, COC, °F	ASTM D 92	200
Fire Point, COC, °F	ASTM D 92	205

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127