

MOLDOL 601 S



DEMOLDING



TOTAL

Concrete Mold Release Oil.

APPLICATIONS

- **MOLDOL 601 S** is a specialized lubricant designed to serve as a concrete release agent for all types of forms. This product is a medium viscosity oil which contains special fatty components that work to form a film that allows easy removal of the forms. Clean, smooth finishes on the concrete and little build-up on the forms is the result.
- **MOLDOL 601 S** does not contain volatile organic compounds (VOC's) that may be restricted for use in some locations.
- **MOLDOL 601 S** is generally applied through automatic spray systems in order to assure a consistent film. However, manual spraying, swabbing, rolling, or brush application is acceptable.

ADVANTAGES

- Ensures good lubricant film.
- Promotes good surface finish.
- Mild petroleum odor.
- Excellent wetting ability.
- Contains no solvent.

TYPICAL CHARACTERISTICS	METHODS	MOLDOL 601 S
Appearance	Visual	Clear Light Pale Liquid
Color	ASTM D 1500	< 2.0
Density @ 60 °F, lbs./gal.	ASTM D 1298	7.47
Specific Gravity @ 60/60 °F	ASTM D 1298	0.895
Lubricity Content, %		> 95.0
Saponification Value		198 - 208
Acid Value		196 - 208
Flash Point, COC, °F	ASTMD 92	> 350

TOTAL Lubricants USA, Inc.

Linden, NJ 07036

5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379

709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914

3315 Riverside Drive
800.323.3198 / 800.526.4127