MULTIS XHV 2





Multi-Purpose, Extreme Pressure, Lithium/Calcium Grease.

APPLICATIONS

Multi-purpose, extreme pressure grease.
General lubrication.

- MULTIS XHV 2 is a multi-purpose grease, formulated for the lubrication of all kinds of applications, operating at medium and slow speeds, where the grease is required to support exceptionally heavy loads in wet, dusty, and/or dry environments.
- MULTIS XHV 2 is commonly used as a grease for the "fifth wheel" in transport applications.
- MULTIS XHV 2 is also suitable as an extreme pressure, multi-purpose grease for slow moving, heavily charged industrial and off-road applications where water is in frequent contact with the grease.
- Always avoid contamination of the grease by dust and/or dirt when applying.
 Preferably use a pneumatic pump system or cartridges.

SPECIFICATIONS

ISO 6743-9: L-XBCHB 2DIN 51502: KP2K-20

ADVANTAGES

Durable lubricant film. No harmful substances.

- Very high base oil viscosity for slow moving, heavily charged applications.
- Miscible with most other conventional soap greases.
- Outstanding adhesion to metal.
- Provides a durable lubricant film.
- Excellent mechanical and thermal stability.
- High resistance to temperature variations.
- Excellent anti-rust and anti-corrosion properties.
- Does not contain lead or any other heavy metals harmful to humans or the environment.

TYPICAL CHARACTERISTICS	METHODS	MULTIS XHV 2
Appearance	Visual	Smooth Pale Brown
Operating Range, °F		0 - 265
Thickener Type		Lithium / Calcium
NLGI Grade		2
Penetration Worked, 60xx	ASTM D 217	265 - 295
Dropping Point, °F	ASTM D 2265	> 365
Four Ball Weld Load, kg	DIN 51350-4	316
SKF-EMCOR anti-rust performance	DIN 51802	0-0
Base Oil Properties:		
Viscosity @ 40°C, cSt	ASTM D 445	1300

TOTAL Lubricants USA, Inc.

Linden, NJ 07036 5 North Stiles Street 908.862.9300/800.526.4127 Rockingham, NC 28379 709 Airport Road 800.323.3198 / 800.526.4127 Knoxville, TN 37914 3315 Riverside Drive 800.323.3198 / 800.526.4127