NEVASTANE® CLEAR 15 & 68





USP White Mineral Oil for the Food and Pharmaceutical Industries.

APPLICATIONS

USP White Mineral Oil.

3H & H1 Registered Food Grade Oil.





- NEVASTANE CLEAR 15 & 68 are made with USP white mineral oil, NSF listed 3H and H1. They are recommended for use as a release agent in food processing plants where there is direct contact with foodstuff, such as dough dividers. These products comply with FDA 21 CFR 172.878 and FDA 21 CFR 178.3620(a). The minimal amount possible should be used to achieve the desired technical effect on the equipment.
- **NEVASTANE CLEAR 15 & 68** oils are suitable for use on machinery used for producing, manufacturing, packing, preparing, and packaging food where there is a possibility of incidental food contact. These products should be used as recommended by a responsible company representative. Prolonged contact with the skin may cause mild irritation. See the Material Safety Data Sheet for additional information.
- NSF 3H, H1 Registered meets USDA 1998 H1 Guidelines for incidental contact with food.

ADVANTAGES

- · Water white.
- Low and high temperature service.
- High temperature stability.
- 3H and H1 registered.
- · Compatible with elastomers and seals.
- · Good film strength.

TYPICAL CHARACTERISTICS	METHODS	NEVASTANE CLEAR	
ISO VG Grade		15	68
NSF Registration Number		139922	140032
Appearance	Visual	Bright, Clear, Water White	
Viscosity @ 40°C, cSt	ASTM D 445	14.2-17.0	65.0-70.0
Saybolt Color, min.		30	30
Flash Point, COC, °F(°C)	ASTM D 92	350(178)	450(234)
Pour Point, °F(°C)	ASTM D 97	10(-12)	10(-12)
Density @ 60°F, lbs./gal.	ASTM D 1298	7.17	7.26
Specific Gravity @ 60°F/60°F	ASTM D 1298	0.859	0.863

TOTAL Lubricants USA, Inc.

Linden, NJ 070365 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914 3315 Riverside Drive 800.323.3198 / 800.526.4127