

OSYRIS 106 S



METALWORKING



TOTAL

Soft Wax Film Rust Preventative.

APPLICATIONS

- **OSYRIS 106 S** is a solvent based rust preventative. It is designed to leave a soft film of wax for positive indoor protection from rust on metal surfaces and precision parts.
- **OSYRIS 106 S** is non-staining, low odor, and can be applied by conventional brush, dip, or spray methods.

ADVANTAGES

- Easily removed from parts with petroleum solvents, by vapor degreasing, or by hot alkaline wash (130 °F).
- Outstanding oxidation resistance.
- Non-staining.
- Excellent metal wetting ability.

| TYPICAL CHARACTERISTICS | OSYRIS 106 S |
|------------------------------------|--------------------|
| | |
| Appearance | Light Amber Liquid |
| Color, ASTM D-1500 | 2.5 |
| Odor | Mild Petroleum |
| Viscosity at 40°C, cSt | < 3.0 |
| Density @ 60 °F, lbs./gal. | 6.60 |
| Specific Gravity @ 60/60 °F | 0.791 |
| Flash Point, COC, °F | 140 |
| Copper Strip Corrosion | 1A-1B |
| Lubricity Content, % | 15.0 |
| Film Type | Soft Wax |
| Humidity Cabinet Test, ASTM D 1748 | 60+ days |
| Indoor Protection, months | 4 - 6 |

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127