


# OSYRIS 211 S



METALWORKING



**TOTAL**

Oily Film Rust Preventative.

## APPLICATIONS

- **OSYRIS 211 S** is a petroleum based rust preventative designed to leave a light, oily, film that prevents rust and corrosion on metal parts and contains a fluorescent dye for easy detection. This film will provide excellent indoor protection from rust and corrosion up to 6 months.
- **OSYRIS 211 S** is a non-staining, low in odor, and non-drying rust preventative. It can be applied by conventional dip, brush, or spray methods.
- Uses include: preservative for work in process, idle, or stored machine tools, parts, dies, jigs, or bearings. Primarily recommended to provide rust protection to steel sheets, coils, bar stock, and can also be used as a "slushing" or "mothballing" oil in engines prior to actual service.

## ADVANTAGES

- Easily removed from parts with petroleum solvents or by vapor degreasing.
- High flash point.
- Displaces water.
- Non-staining.
- Excellent metal wetting ability.
- Enhanced oxidation resistance.
- Fluorescent dye for easy detection.

TYPICAL CHARACTERISTICS	OSYRIS 211 S
Appearance	Light Pale Liquid
Color, ASTM D-1500	1.0
Odor	Mild Petroleum
Viscosity at 40°C, cSt	25.2 - 30.8
Density @ 60 °F, lbs./gal.	7.25
Specific Gravity @ 60/60 °F	0.871
Flash Point, COC, °F	405
Copper Strip Corrosion	1A-1B
Lubricity Content, %	2.0
Film Type	Oily
Indoor Protection, months	5 - 6

TOTAL Lubricants USA, Inc.

Linden, NJ 07036  
5 North Stiles Street  
908.862.9300/800.526.4127

Rockingham, NC 28379  
709 Airport Road  
800.323.3198 / 800.526.4127

Knoxville, TN 37914  
3315 Riverside Drive  
800.323.3198 / 800.526.4127