

PRESLIA SE JET



Turbine



Synthetic oil for aeroderivatives turbines.

APPLICATIONS

Aeroderivatives turbines

- Lubrication and regulation of extremely high-performance aeroderivatives turbines.

SPECIFICATIONS

International standards Manufacturers

- **PRESLIA SE JET** is approved according to the following international standards on turbines manufacturers:
 - MIL-PRF-23699F
 - ALLISON ROLLS ROYCE (USA)
 - GENERAL ELECTRIC
 - ROLLS ROYCE (UK)
 - TURBOMECA

ADVANTAGES

High running safety level Extended oil bath lifetime

- **PRESLIA SE JET** owns all the properties required to ensure the lubrication of the aeroderivative turbines working in the most difficult conditions :
 - Very high viscosity index
 - Excellent ability to withstand high temperatures
 - Excellent anti-oxidant capability
 - Excellent ability to withstand low temperatures
 - Very high anti-corrosion anti-foaming properties.

TYPICAL CHARACTERISTICS	METHODS	UNITS	PRESLIA SE JET
Density at 15 °C	ISO 3675	kg/m ³	998
Viscosity at - 40 °C	ASTM D 2532	mm ² /s	9400
Viscosity at 40 °C	ISO 3104	mm ² /s	25.1
Viscosity at 100 °C	ISO 3104	mm ² /s	5.1
Viscosity index	ISO 2909	-	135
Pour point	ISO 3016	°C	- 60
Cleveland flash point	ISO 2592	°C	265
Fire point	ISO 2592	°C	300
Self-ignition point		°C	403

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS Industrie & Spécialités

21-06-2007 (supersedes 14-05-2001)

PRESLIA SE JET

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.