

- performance
- Good efficiency against bore polishingExcellent viscosity stability in operation
- High detergency and excellent soot dispersion

CHARACTERISTICS

TYPICAL CHARACTERISTICSRUBIA TIR 7900 SB NA SAE 15W-40			
Specific gravity at 60/60 F (ASTM D 1298)	0.869	Pour point, °F (°C) (ASTM D 97)	-29 (-34)
Viscosity @ 40°C, cSt (ASTM D 445)	99.6	Flash point °F (°C) (ASTM D 92)	403 (206)
Viscosity @ 100°C, cSt (ASTM D 445)	14.8	Phosphorus (ppm)	< 1200
Viscosity Index (ASTM D 2270)	154	Ash, wt% (ASTM D 874)	1.0
Cold crank, cps @ -20°C (ASTM D 5293)	< 7000	TBN (ASTM D 2896)	10

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418, Plano, Texas 75075 800-442-5823 or 469-241-0950 www.total-us.com

Rubia TIR 7900 SB NA 15W-40 Sheet updated: 5/10/2010 5 North Stiles Street Linden, NJ 07036 908.862.9300 or 800.526.4127 www.total-us.com

TOTAL Lubricants USA with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. MSDS are found on our web sites.