

SJ-33 TRACTOR HYDRAULIC



FLUID

LUBRICATION



TOTAL

Tractor Hydraulic Fluid.

APPLICATIONS

All major brands of tractors and other farm equipment.

- **SJ-33 TRACTOR HYDRAULIC FLUID** is a premium grade fluid specially designed for use in transmissions, final drives, wet brakes, and hydraulic systems of all major brands of tractors and other farm implements employing a common fluid reservoir.

SPECIFICATIONS

International Specifications

- API SERVICE DESIGNATIONS: GL-4
- JOHN DEERE J20C
- MASSEY FERGUSON M1141
- FORD NEW HOLLAND M2C134D
- WHITE FARM
- KUBOTA
- CATERPILLAR TO-2
- CASE INTERNATIONAL

ADVANTAGES

- Excellent water tolerance characteristics.
- Compatibility with seals, pump materials, and copper components.
- Eliminates brake chatter.
- Excellent filterability and low temperature properties.
- Proper friction characteristics for PTO, clutches, and wet brakes.
- Smooth engagement of transmission clutch plates.

TYPICAL CHARACTERISTICS	METHODS	SJ-33 TRACTOR HYDRAULIC
Appearance	Visual	Clear Liquid
Viscosity at 40°C, cSt	ASTM D 445	60.0
Viscosity at 100°C, cSt	ASTM D 445	9.3 - 12.5
Brookfield Viscosity, cP	ASTM D 2983	4100 (-20°C), 49,500(-35°C)
Shear Stability Viscosity @ 100°C		7.75
Viscosity Index	ASTM D 2270	150
Flash Point, COC, °F(°C)	ASTM D 92	437(225)
Pour Point, °C	ASTM D 97	-38
Density @ 60 °F, lbs./gal.	ASTM D 1298	7.36
Specific Gravity @ 60/60°F	ASTM D 1298	0.884
Copper Corrosion	ASTM D 130	1A
Allison Approval Number		C4-16040991

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.227.1979

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127