## **SPIRIT 995 S**



METALWORKING



## Heavy Duty, Emulsifiable Metalworking Fluid for All Metals.

APPLICATIONS	• <b>SPIRIT 995 S</b> is an emulsifiable coolant specially formulated for most all heavy duty machining and grinding applications including automotive cast aluminum. This product is specially formulated to provide exceptional biological control
ADVANTAGES	<ul> <li>Extreme pressure and anti-wear agents.</li> <li>Excellent cooling and wetting properties</li> <li>Non-foaming, non-staining, non-flammable, non-irritating and non-toxic</li> <li>Very good success in roll tapping of aluminum alloys.</li> <li>Splits out tramp oil quickly.</li> <li>Settles metal fines rapidly and keeps grinding wheels clean.</li> <li>Excellent for recycling.</li> <li>Versatile</li> <li>Superior surface finish</li> </ul>

TYPICAL CHARACTERISTICS	SPIRIT 995 S
Appearance	Amber Liquid
Density @ 60 °F, lbs./gal.	8.1
Flash Point, COC, °F	None
Refractometer factor	1.1
pH @ 10% with 17grain hardness	9.2 - 9.4

## **Directions For Use-**

Honing, Tapping, Reaming = 7 - 10%Milling, Drilling, Turning = 5 - 7%Centerless I.D. O.D. Grinding = 3 - 5%

Issue Date: 8302012DL

## **TOTAL Lubricants USA, Inc.**

*Linden, NJ 07036* 5 North Stiles Street 908.862.9300/800.526.4127 **Rockingham, NC 28379** 709 Airport Road 800.323.3198 / 800.526.4127

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2008 All rights reserved. JAS 09/2008