TRANSMISSION SYN SAE 50





Eaton/Meritor approved fuel economy transmission oil

APPLICATIONS

Types of service

 TRANSMISSION SYN SAE 50 is a specially formulated synthetic lubricant designed for extended drain and severe service in heavy duty manual transmissions which require a non EP gear or transmission lubricant. It is specially formulated to protect the higher torque manual transmissions coupled with the increased horsepower engines.

PERFORMANCE

Specifications

- API MT-1
- Eaton Approved PS 164 REV 7
- International TMS-6816
- Mack TO-A PLUS
- Meritor Automotive/Rockwell International 0-81
- Navistar TMS 6816

CUSTOMER BENEFITS

Extended drain service

High technical performance

- Extended drain intervals (500,000 miles)
- · Extended warranty coverage at Eaton and Meritor
- · All climate year around performance
- · Potential for fuel economy
- Oxidation, rust and corrosion inhibited and foam resistant

CHARACTERISTICS

| TYPICAL PROPERTIES TRANSMISSION SYN SAE 50 | |
|--|-----------------|
| Specific gravity at 60/60 °F (lbs./gal.) ASTM D 1298 | 0.860 (7.16) |
| Viscosity @ 40 °C, cSt ASTM D-445 | 132 |
| Viscosity @ 100 °C, cSt ASTM D-445 | 17.5 |
| Viscosity index ASTM D-2270 | 146 |
| Flash point, °F (°C) ASTM D-92 | 430 (221) |
| Brookfield viscosity, cps ASTM D-2983 | 104,000 @ -40°C |
| Pour Point °F (°C) ASTM D-97 | -49 (-45) |
| Canadian Channel point °F (°C) FTMS 3456 | <-50 (-46) |

TOTAL Lubricants USA, Inc.