



METALWORKING



Chlorine-free Cutting Oil for General Machining.



- VALONA 132 S is a clear, yellow oil of very light viscosity which is efficient over a wide working range of both metals and machining operations.
- VALONA 132 S is used for light duty metalworking operations and general purpose lubricating applications. It is preferred for machining brass, aluminum, and copper alloys.

ADVANTAGES

- Chlorine/sulfur/phosphorus free.
- Rust and oxidation inhibited.
- Increases tool life.
- Excellent metal wetting ability.
- Superior parts finish.
- Anti-wear and anti-weld characteristics.

TYPICAL CHARACTERISTICS	VALONA 132 S
Appearance	Pale Yellow Liquid
Color, ASTM D-1500	0.5
Viscosity at 40°C, cSt	13.5 - 16.5
Density @ 60 °F, lbs./gal.	7.29
Specific Gravity @ 60/60 °F	0.875
Flash Point, COC, °F	345
Lubricity Content, %	20.0
Copper Strip Corrosion	1A-1B
Sulfur Content, %wt.	Nil
Chlorine Content, %wt.	Nil

TOTAL Lubricants USA, Inc.

Linden, NJ 07036 5 North Stiles Street 908.862.9300/800.526.4127

Rockingham, NC 28379 709 Airport Road 800.323.3198 / 800.526.4127 Knoxville, TN 37914 3315 Riverside Drive 800.323.3198 / 800.526.4127

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2008 All rights reserved. JAS 09/2008